Line-oriented programming: `awk`

Three versions of `awk` (named after its authors — Aho, Weinberger and Kernighan): `nawk` ("new `awk`") is more powerful than `awk` and `gawk` (GNU `awk`) is even more powerful. I will focus on `gawk`.

Starting `gawk`

`gawk` *options* '*program*' *file* or
`gawk` *options* `-f` *program_file file*
When *file* is omitted, `awk` uses its standard input. It's possible to give several `-f` options.

`awk` variables

`NF`	number of fields (in the current line)
`NR`	number of records (lines) seen so far
`FS`	input field separator (see `-F` option)
`RS`	input record separator (newline)
`$`*`expression`*	the whole input line, when *`expression`* equals 0
`$`*`expression`*	the i-th field, when *`expression`* equals i

`gawk` options

`-F` *`fs`*	Specify field separator (reg.expr.)
`-v` *`var=val`*	Set variable

`awk` commands

Awk command has the form:

condition { *action* }

`awk` conditions

`BEGIN` or `END` or /*reg.expr.*/ or a relation (e.g., `(NF>3)`) or a boolean expression over regular expressions and relations (e.g. `(/a.*c/ && (NF>3))`).

`awk` actions

if (*condition*) *statement*

variable=*expression*

print *expression*

print *expression redirection*

next

{ $statement_1$; ... ; $statement_n$ }

Example: HW2 grade confirmation script

```
#!/usr/local/gnu/bin/gawk -f
/^HW2-User: / {USER=$2; next}
/^HW2-Path: / {PATH=$2; next}
/^HW2-Total: / {GRADE=$2; next}
{next}
END {
   print "Grade: " GRADE " User: " USER " Path: " PATH >> \
      "/home/cs114/hw2/part";
   MAIL = "/usr/lib/sendmail " USER "@cornell.edu";
   print "Subject: CS114 HW2 Confirmation" | MAIL;
   print "From: nogin@cs.cornell.edu" | MAIL;
   print "To: " USER "@cornell.edu\n" | MAIL;
   print "Preliminary HW2 grade: " GRADE | MAIL;
   close MAIL
}
```

```
#!/usr/local/gnu/bin/gawk -f
{
   if (($1,$3) in saw) {
      print "Warning: duplicate " $1 " for " $3 > "/dev/stderr";
   } else {
      saw[$1,$3]="yes";
      num[$3]++;
      total[$3]+=$4;
      grade[$3,num[$3]]=$4;
      grades[$3,$4]++;
      all_grades[$4]++;
   }
}

END {
   for (i in num) {
      print "Part " i ":";
      print "   " num[i] " students";
      print "   average: " total[i]/num[i];
      print "   median: " grade[i,int(num[i]/2)];
      print "   stats:";
      sort = "sort -n";
      for (j in all_grades) if ((i,j) in grades) {
            printf "      " j " --- " grades[i,j] " student" | sort;
            if (grades[i,j]>1) print "s" | sort; else print "" | sort;
      }
      close (sort);
   }
}
```

Stream editor — `sed`

`sed -e 'script'` *`file`* or texttt**sed** -f *script_file file*
It's possible to give several `-e` options. When *`file`* is omited, the standard input is used.

`sed` substitution command

`s/`*`reg.expr.`*`/`*`subst.expr.`*`/`*`options`*
It can be prefixed by a *`range`* that has a form *`addr`*`,`*`addr`*