

Recitation 4

Enums and
The Java Collections classes

1

Enums

How do we represent . . .

- Suits - Clubs, Spades, Diamonds, Hearts
- Directions - North, South, East, West
- Days of week - Monday, Tuesday . . .
- Planets - Mercury, Venus, Earth . . .

Other small sets of values that do not change

2

Enums

Using constants

```
public class Suit {
    public static final int CLUBS= 0;
    public static final int SPADES= 1;
    public static final int DIAMONDS= 2;
    public static final int HEARTS= 3;
}
```

Problems:

- no type checking
- readability

```
void setSuit(int suit) {...}
int getSuit() {...}
```

3

Enums

Better way: Objects as constants

```
public class Suit {
    public static final Suit CLUBS= new Suit();
    public static final Suit SPADES= new Suit();
    public static final Suit DIAMONDS= new Suit();
    public static final Suit HEARTS= new Suit();

    private Suit() {}
}
```

cannot modify Suit objects

no new Suits can be created

Suit v; ... if (v == Suit.CLUBS) { ... } must use ==

4

Enums

Enum (enumeration) declaration

can be any access modifier

```
public enum Suit {CLUBS, SPADES, DIAMONDS, HEARTS};
```

new keyword

name of enum

static final variables of enum Suit

5

Enums

About enums

1. Can contain methods, fields, constructors
 - `Suit.HEARTS.getColor();`
1. Suit's constructor is private!
 - Cannot instantiate except for initial constants
1. `Suit.values()` returns a `Suit[]` of constants in the `enum`

6

Enums

Demo: Enums in action

Look at **enum** Suit.

Create a class PlayingCard and a class Deck.

What would be the fields for a PlayingCard object?

7

Enums

Enum odds and ends

1. Suit is a subclass of `java.lang.Enum`
2. `ordinal()` returns position in list (i.e. the order it was declared)
 - a. `Suit.CLUBS.ordinal() == 0`
3. enums automatically implement Comparable
 - a. `Suit.CLUBS.compareTo(Suit.HEARTS)` uses the ordinals for Clubs and Hearts
4. `toString()` of `Suit.CLUBS` is "CLUBS"
 - a. you can override this!

8

Enums

Enum odds and ends

5. **switch** statement

```
Suit s = Suit.CLUBS;
switch(s) {
    case CLUBS:
        color= "black"; break;
    case SPADES:
        color= "black"; break;
    case DIAMONDS:
        color= "black"; break;
    case HEARTS:
        color= "red"; break;
}
```

`s == Suit.CLUBS` is true

switch statements are fall through! break keyword is necessary.

9

Collections and Maps

The Collections classes and interfaces that come with Java provide implementations of

- bags (a.k.a. multiset – sets with repeated values)
- sets (and sorted sets)
- lists
- stacks
- queues
- maps (and sorted maps) [like dictionaries]

You will see in later assignments how easy it is to use these

10

ArrayList as example of structure

Class ArrayList implements a list in an array that can grow and shrink. Example of code:

```
ArrayList<Integer> t= new ArrayList<Integer>();
t.add(5);
t.add(7);
System.out.println(t.get(0)); // prints 5
t.add(0, 2); // insert 2 at index 0, shifting other
// values up. Can be costly.
System.out.println(t); // prints [2, 5, 7]
```

11

Collections and Map

Power of inheritance and interfaces

```

graph TD
    Object --> AbstractCollection["AbstractCollection<E>"]
    AbstractCollection --> AbstractList["AbstractList<E>"]
    AbstractList --> ArrayList["ArrayList<E>"]
    AbstractCollection --> Iterable["Iterable<E>"]
    AbstractCollection --> Collection["Collection<E>"]
    AbstractList --> List["List<E>"]
    ArrayList --> List
    
```

Format of ArrayList object

12

Collections and Map

Important interfaces, some methods in them

Collection<E>

```
add(E);
contains(Object);
isEmpty();
remove(Object);
size();
...
```

No new methods in Set<E>, just changes specifications

Map<K,V>

```
put(K,V);
get(Object);
```

List<E>

```
get(int);
indexOf(int);
add(int,E);
...
```

Set<E>

13

Collections and Map

Important classes and interfaces

```

graph TD
    C[Collection<E>] --> S[Set<E>]
    C --> L[List<E>]
    S --> HS[HashSet<E>]
    L --> LL[LinkedList<E>]
    L --> AL[ArrayList<E>]
    M[Map<K,V>] --> HM[HashMap<K,V>]
    
```

14

Collections and Map

Queues? Stacks?

```

graph TD
    C[Collection<E>] --> Q[Queue<E>]
    C --> D[Deque<E>]
    Q --> D
    D --> LL[LinkedList<E>]
    D --> AD[ArrayDeque<E>]
    
```

Deque:
Double-Ended Queue

15

Collections and Map

Iterating over a HashSet or ArrayList

```

HashSet<E> s = new HashSet<E>();
... store values in the set ...
for (E e : s) {
    System.out.println(e);
}
    
```

Object

Fields contain a set of objects

```
add(E)
contains(Object)
remove(Object)
size()
...
```

Body of loop is executed once with **e** being each element of the set. Don't know order in which set elements are processed

16

Collections and Map

Collections problems

1. Remove duplicates from an array
2. Find all negative numbers in array
3. Create ransom note
4. Implement a Stack with a max API
5. Braces parsing

17

Collections and Map

Collections problems

Complete

```
Integer[] removeDuplicates (int [])
```

Remove all duplicates from an array of integers.

Very useful HashSet method:

```
hs.toArray(new Integer[hs.size()]);
```

18

Collections problems

Find Negative Numbers

Find all negative numbers in array and return an array with those integers

Very useful ArrayList method:

```
lst.toArray(new Integer[lst.size()]);
```

19

Collections problems

Create Ransom Note

Given a note (String) that you would like to create and a magazine (String), return whether you can create your note from the magazine letters.



20

Collections problems

Implement a Stack<E> with a max() function in O(1) time

No matter how full the stack is, the max function should be in constant time. (ie you should not iterate through the Linked List to find the maximum element)

21

Collections problems

Braces parsing in O(n) time

Return whether a String has the right format of square brackets and parenthesis.

e.g.
`"array[4] = ((new Integer(3)));"` <- is true
`"() []"` <- is false
`"(" <- is false
" ([] " <- is false`

22