

CS1110 12 Mar 2009 Arrays. Reading: Secs 8.1, 8.2, 8.3

Listen to the following lectures on loops on your Plive CD. They are only 2-3 minutes long, and each has an insightful message.

- The 3 lectures on Lesson page 7-6 — read the whole page.
- The 4 lectures in Lesson page 7-5.

Computational simplicity

Most of us don't write perfect essays in one pass, and coding is the same: writing requires revising; programming requires revising.

If you are writing too much code — it gets longer and longer, with no end in sight: *stop and look for a better way.*

If your code is getting convoluted and you have trouble understanding it: *stop and look for a better way.*

Learn to keep things simple, to solve problems in simple ways. This sometimes requires a different way of thinking.

We are trying to teach not just Java but how to think about problem solving.

A key point is to break a problem up into several pieces and do each piece in isolation, without thinking about the rest of them. Our methodology for developing a loop does just that.

```

/* day contains the number of days
   since ORIGINYEAR (1 Jan 1980)
*/
/* Set year to current year and day to
   current day of current year */
year = ORIGINYEAR; /* = 1980 */

```

Zune error <http://tinyurl.com/9b4hmy>

On 31 Dec 2008, the Zune stopped working. Anger!
On 1 Jan 2009 it worked.

```

while (day > 365) {
  if (IsLeapYear(year)) {
    if (day > 366) {
      day = day - 366;
      year = year + 1;
    }
  } else {
    day = day - 365;
    year = year + 1;
  }
}

```

Zune clock code keeps time in seconds since beginning of 1980. It calculates current day and year from it.

Example	year	day
Does each iteration make progress toward termination?	1980	738
Not if days == 366!!	1981	372
	1982	7

Array: object. Can hold a fixed number of values of the same type. Array contains 4 **int** values.

The **type** of the array:

```
int[]
```

Variable contains name of the array. `x` `a0` `int[]`

Basic form of a declaration:

```
<type> <variable-name>;
```

A declaration of `x`. `int[] x;`

Does not create array, it only declares `x`. `x`'s initial value is **null**.

Elements of array are numbered: 0, 1, 2, ..., `x.length-1`;

Make everything as simple as possible, but no simpler. Einstein

a0
0
5
1
7
2
4
3
-2

Notes on array length

Array length: an instance field of the array.

This is why we write `x.length`, not `x.length()`

Length field is **final**: cannot be changed.

Length remains the same once the array has been created.

We omit it in the rest of the pictures.

The length is not part of the array type.

The type is `int[]`

An array variable can be assigned arrays of different lengths.

a0	length
0	4
5	
1	7
2	4
3	-2

`int[] x;` `x` `null` `int[]`

`x = new int[4];` Create array object of length 4, store its name in `x`

`x` `a0` `int[]`

`x[2] = 5;` Assign 5 to array element 2 and
`x[0] = -4;` -4 to array element 0

`x[2]` is a reference to element number 2 of array `x`

`int k = 3;`
`x[k] = 2 * x[0];` Assign $2 * x[0]$, i.e. -8, to `x[3]`
`x[k-1] = 6;` Assign 6 to `x[2]`

Arrays

a0
0
0
1
0
2
0
3
0

a0
0
-4
1
0
2
5
3
0

a0
0
-4
1
0
2
6
3
-8

Difference between Vector and array

Declaration: `int[] a;` Vector `v;`

Elements of `a`: **int** values Elements of `v`: any Objects

Creation: `a = new int[n];` `v = new Vector();`

Array always has `n` elements Number of elements can change

Reference: `a[e]` `v.get(e)`

Change element: `a[e] = e1;` `v.set(e, e1);`

Array locations `a[0], a[1], ...` in successive locations in memory. Access takes same time no matter which one you reference.

Elements all the same type (a primitive type or class type)

Can't tell how Vectors are stored in memory. Referencing and changing elements done through method calls which one you reference.

Elements of any Object type (but not a primitive type). Casting may be necessary when an element is retrieved.

Array initializers

Instead of

```
int[] c= new int[5];
c[0]= 5; c[1]= 4; c[2]= 7; c[3]= 6; c[4]= 5;
```

Use an array initializer:

```
int[] c= new int[] {5, 4, 7, 6, 5};
```

a0
5
4
7
6
5

No expression between brackets [].
(can omit this)

array initializer: gives values to be in the array initially. Values must have the same type, in this case, **int**. Length of the array is the number of values in the list

Computer science has its field called computational complexity; mine is called computational simplicity. Gries

Use of an array initializer

```
public class D {
    public static final String[] months= new String[]{"January", "February",
        "March", "April", "May", "June", "July", "August",
        "September", "October", "November", "December"};

    /** = the month, given its number m
        Precondition: 1 <= m <= 12 */
    public static String theMonth(int m) {
        return months[m-1];
    }
}
```

Months[m-1] is returned, since
months[0] = "January",
months[1] = "February",
...

Variable months is:
static: object assigned to it will be created only once.
public: can be seen outside class D.
final: it cannot be changed.

Linear search

```
public class D {
    /** = index of first occurrence of c in b[h..]
        Precondition: c is guaranteed to be in b[h..] */
    public static int findFirst (int c, int[] b, int h) {
        // Store in i the index of first c in b[h..]
        int i= h;
        // invariant: c is not in b[h..i-1]
        while ( c != b[i] ) {
            i= i + 1;
        }
        // b[i] = c and c is not in b[h..i-1]
        return i;
    }
}
```

Remember
h..h-1 is the empty range

Loopy questions:
1. initialization?
2. loop condition?
3. Progress?
4. Keep invariant true?

invariant

h	i	k
c is not here	c	

h	i	k
c is not here	c is in here	

```
/** = a random int in 0..p.length-1, assuming p.length > 0.
    The (non-zero) prob of int i is given by p[i].*/
public static int roll(double[] p) {
    double r= Math.random(); // r in [0,1)
    /** Store in i the segment number in which r falls. */
    int i = 0;    double iEnd= p[0];
    // inv: r is not in segments looked at (segments 0..i-1)
    // and iEnd is the end of (just after) segment i
    while ( r not in segment i ) {
        r >= iEnd
        iEnd= iEnd + p[i+1];
        i= i + 1;
    }
    // r is in segment i
    return i;
}
```

It's a linear search!

1. init
2. condition
3. progress
4. invariant true

0	p[0]	p[0]+p[1]	1

Procedure swap

```
public class D {
    /** = Swap x and y */
    public static void swap (int x, int y) {
        int temp= x;
        x= y;
        y= temp;
    }
}
```

A call will NOT swap a and b. Parameters x and y are initialized to the values of a and b, and thereafter, there is no way to change a and b.

a [5] b [3]

swap: 1	?
x [5] y [3]	
temp [?]	

frame for call just after frame created and args assigned to pars:

Procedure swap

```
public class D {
    /** = Swap b[h] and b[k] */
    public static void swap (int[] b, int h, int k) {
        int temp= b[h];
        b[h]= b[k];
        b[k]= temp;
    }
}
```

Does swap b[h] and b[k], because parameter b contains name of the array.

c [a0]

swap: 1	?
b [a0] h [3]	
temp [?] k [4]	

a0
5
4
7
6
5

frame for call just after frame is created.