


CS/ENGRD 2110 Object-Oriented Programming and Data Structures

Spring 2011
Thorsten Joachims

Lecture 14: Graphical User Interfaces (Dynamic)



GUI Statics and GUI Dynamics

- Statics: what's drawn on the screen
 - Components
 - E.g. buttons, labels, lists, sliders, menus, ...
 - Containers
 - components that contain other components
 - E.g. frames, panels, dialog boxes, ...
 - Layout managers
 - control placement and sizing of components
- Dynamics: user interactions
 - Events
 - E.g. button-press, mouse-click, key-press, ...
 - Listeners
 - an object that responds to an event
 - Helper classes
 - E.g. Graphics, Color, Font, FontMetrics, Dimension, ...

2

Dynamics Overview

- Dynamics = causing and responding to actions
 - What actions?
 - Called events: mouse clicks, mouse motion, dragging, keystrokes
 - We would like to write code (a handler) that is invoked when an event occurs so that the program can respond appropriately
 - In Java, you can intercept events by providing an object that "hears" the event – a listener
 - What objects do we need to know about?
 - Events
 - Event listeners

3

Brief Example Revisited

```
import javax.swing.*;
import java.awt.*;
import java.awt.event.*;

public class Intro extends JFrame {
    private int count = 0;
    private JButton myButton = new JButton("Push Me!");
    private JLabel label = new JLabel("Count: " + count);

    public Intro() {
        setDefaultCloseOperation(EXIT_ON_CLOSE);
        setLayout(new FlowLayout(FlowLayout.LEFT)); //set layout manager
        add(myButton); //add components
        add(label);
        label.setPreferredSize(new Dimension(60, 10));
        myButton.addActionListener(new ActionListener() {
            public void actionPerformed(ActionEvent e) {
                count++;
                label.setText("Count: " + count);
            }
        });
    }
    pack();
    setVisible(true);
}

public static void main(String[] args) {
    new Intro();
}
```



4

The Java Event Model

- Timeline
 - User or program does something to a component
 - clicks on a button, resizes a window, ...
 - Java issues an event object describing the event
 - A special type of object (a listener) "hears" the event
 - The listener has a method that "handles" the event
 - The handler does whatever the programmer programmed
- What you need to understand
 - Events: How components issue events
 - Listeners: How to make an object that listens for events
 - Handlers: How to write a method that responds to an event

5

Events

- An Event is a Java object
- Events are normally created by the Java runtime system
 - You can create your own, but this is unusual
- Normally events are associated with a component
- Most events are in `java.awt.event` and `javax.swing.event`
- All events are subclasses of `AWTEvent`
- Event types:
 - ActionEvent
 - AdjustmentEvent
 - ComponentEvent
 - ContainerEvent
 - FocusEvent
 - HierarchyEvent
 - InputEvent
 - InputMethodEvent
 - InvocationEvent
 - ItemEvent
 - KeyEvent
 - MouseEvent
 - MouseWheelEvent
 - PaintEvent
 - TextEvent
 - WindowEvent

6

Types of Events

- Each Swing Component can generate one or more types of events
 - The type of event depends on the component
 - Clicking a `JButton` creates an `ActionEvent`
 - Clicking a `JCheckbox` creates an `ItemEvent`
 - The different kinds of events include different information about what has occurred
 - All events have method `getSource()` which returns the object (e.g., the button or checkbox) on which the Event initially occurred
 - An `ItemEvent` has a method `getStateChange()` that returns an integer indicating whether the item (e.g., the checkbox) was selected or deselected

7

Event Listeners

- **ActionListener, MouseListener, WindowListener, ...**
- Listeners are Java interfaces
 - Any class that implements that interface can be used as a listener
- To be a listener, a class must implement the interface
 - E.g. an `ActionListener` must contain a method `public void actionPerformed(ActionEvent e)`

8

Implementing Listeners

- Which class should be a listener?
 - Java has no restrictions on this, so *any* class that implements the listener will work
- Typical choices:
 - Top-level container that contains whole GUI


```
public class GUI implements ActionListener
```
 - Inner classes to create specific listeners for reuse


```
private class LabelMaker implements ActionListener
```
 - Anonymous classes created on the spot


```
b.addActionListener(new ActionListener() {...});
```

9

Listeners and Listener Methods

- When you implement an interface, you must implement all the interface's methods
 - Interface `ActionListener` has one method:
 - `void actionPerformed(ActionEvent e)`
 - Interface `MouseListener` has five methods:
 - `void mouseClicked(MouseEvent e)`
 - `void mouseEntered(MouseEvent e)`
 - `void mouseExited(MouseEvent e)`
 - `void mousePressed(MouseEvent e)`
 - `void mouseReleased(MouseEvent e)`
 - Interface `MouseMotionListener` has two methods:
 - `void mouseDragged(MouseEvent e)`
 - `void mouseMoved(MouseEvent e)`

10

Registering Listeners

- How does a component know which listener to use?
- You must *register* the listeners
 - This connects listener objects with their source objects
 - Syntax: `component.add???Listener(Listener)`
 - You can register as many listeners as you like
- Example:

```
b.addActionListener(new ActionListener() {
    public void actionPerformed(ActionEvent e) {
        count++;
        label.setText(generateLabel());
    }
});
```

11

Example 1: The Frame is the Listener

```
import javax.swing.*; import java.awt.*; import java.awt.event.*;
public class ListenerExample1 extends JFrame implements ActionListener {
    private int count;
    private JButton b = new JButton("Push Me!");
    private JLabel label = new JLabel("Count: " + count);
    public static void main(String[] args) {
        JFrame f = new ListenerExample1();
        f.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        f.setSize(200,100);
        f.setVisible(true);
    }
    public ListenerExample1() {
        setLayout(new FlowLayout(FlowLayout.LEFT));
        add(b); add(label);
        b.addActionListener(this);
    }
    public void actionPerformed(ActionEvent e) {
        count++;
        label.setText("Count: " + count);
    }
}
```

Example 2: The Listener is an Inner Class

```
import javax.swing.*; import java.awt.*; import java.awt.event.*;
public class ListenerExample2 extends JFrame {
    private int count;
    private JButton b = new JButton("Push Me!");
    private JLabel label = new JLabel("Count: " + count);
    class Helper implements ActionListener {
        public void actionPerformed(ActionEvent e) {
            count++;
            label.setText("Count: " + count);
        }
    }
    public static void main(String[] args) {
        JFrame f = new ListenerExample2();
        f.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        f.setSize(200,100); f.setVisible(true);
    }
    public ListenerExample2() {
        setLayout(new FlowLayout(FlowLayout.LEFT));
        add(b); add(label);
        b.addActionListener(new Helper());
    }
}
```

13

Example 3: The Listener is an Anonymous Class

```
import javax.swing.*; import java.awt.*; import java.awt.event.*;
public class ListenerExample3 extends JFrame {
    private int count;
    private JButton b = new JButton("Push Me!");
    private JLabel label = new JLabel("Count: " + count);
    public static void main (String[] args) {
        JFrame f = new ListenerExample3();
        f.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        f.setSize(200,100); f.setVisible(true);
    }
    public ListenerExample3() {
        setLayout(new FlowLayout(FlowLayout.LEFT));
        add(b); add(label);
        b.addActionListener(new ActionListener() {
            public void actionPerformed (ActionEvent e) {
                count++;
                label.setText("Count: " + count);
            }
        });
    }
}
```

14

Adapters

- Some listeners (e.g., **MouseListener**) have lots of methods; you don't always need all of them
 - For instance, you may be interested only in mouse clicks
- For this situation, Java provides “adapters”
 - An adapter is a predefined class that implements all the methods of the corresponding Listener
 - Example: **MouseAdapter** is a class that implements all the methods of interfaces **MouseListener** and **MouseMotionListener**
 - The adapter methods do nothing
 - To easily create your own listener, you extend the adapter class, overriding just the methods that you actually need

15

Using Adapters

```
import javax.swing.*; import javax.swing.event.*;
import java.awt.*; import java.awt.event.*;
public class AdapterExample extends JFrame {
    private int count; private JButton b = new JButton("Mouse Me!");
    private JLabel label = new JLabel("Count: " + count);
    class Helper extends MouseAdapter {
        public void mouseEntered(MouseEvent e) {
            count++;
            label.setText("Count: " + count);
        }
    }
    public static void main(String[] args) {
        JFrame f = new AdapterExample();
        f.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE);
        f.setSize(200,100); f.setVisible(true);
    }
    public AdapterExample() {
        setLayout(new FlowLayout(FlowLayout.LEFT));
        add(b); add(label);
        b.addMouseListener(new Helper());
    }
}
```

16

Notes on Events and Listeners

- A single component can have many listeners
- Multiple components can share the same listener
 - Can use **event.getSource()** to identify the component that generated the event
- For more information on designing listeners, see <http://download.oracle.com/javase/tutorial/uiswing/events/>
- For more information on designing GUIs, see <http://download.oracle.com/javase/tutorial/uiswing/>

17

GUI Drawing and Painting

- For a drawing area, extend **JPanel** and override the method


```
public void paintComponent(Graphics g)
```

 - **paintComponent** contains the code to completely draw *everything* in your drawing panel
 - Do not call **paintComponent** directly – instead, request that the system redraw the panel at the next convenient opportunity by calling **panel.repaint()**
 - **repaint()** requests a call **paintComponent()** “soon” (i.e. within milliseconds)

18

Java Graphics

- The **Graphics** class has methods for colors, fonts, and various shapes and lines
 - `setColor(Color c)`
 - `drawOval(int x, int y, int width, int height)`
 - `fillOval(int x, int y, int width, int height)`
 - `drawLine(int x1, int y1, int x2, int y2)`
 - `drawString(String str, int x, int y)`
- Take a look at
 - `java.awt.Graphics` (for basic graphics)
 - `java.awt.Graphics2D` (for more sophisticated control)
 - The 2D Graphics Trail:
<http://java.sun.com/docs/books/tutorial/2d/>
 - examples on the web site

19