Lecture 2

Variables & Assignment

Announcements for Today

If Not Done Already

- Enroll in Piazza
- Sign into CMS
  - Fill out the Survey
  - Complete AI Quiz
- (**Optional**) textbook
  - Chapter 1 (browse)
  - Chapter 2 (in detail)

Lab 1

- Please stay in your section
  - If you drop, you are **stuck**
  - E-mail conflicts to Amy
  - ahf42@cornell.edu
  - Will review by next week
- Have one week to complete
  - Fill out questions on handout
  - Show to TA **before** next lab
  - Show in *consulting hours*

Helping You Succeed in this Class

- **Consultants.** ACCEL Lab Green Room
  - Daily office hours (see website) with consultants
  - Very useful when working on assignments
- **AEW Workshops**. Additional discussion course
  - Runs parallel to this class – completely optional
  - See website; talk to advisors in Olin 167.
- **Piazza.** Online forum to ask and answer questions
  - Go here first **before** sending question in e-mail
- **Office Hours.** Talk to the professor!
  - Available in Carpenter Hall Atrium between lectures

Labs vs. Assignments

Labs

- Held every week
- Graded on **completeness**
  - Always S/U
  - Try again if not finished
- Indirect affect on grade
  - Can miss up to 2 labs
  - After that, grade reduced
- Similar to language drills
  - Simple, but take time

Assignments

- Every two weeks
  - First one due Sep. 18
- Graded on **correctness**
  - Assign points out of 100
- But **first** one is for *mastery*
  - Resubmit until perfect grade
- 40% of your final grade
- Designed to be more fun
  - Graphics, game design

iClickers

- Have you registered your iclicker?
- If not, visit
  - http://atcsupport.cit.cornell.edu/pollsrvc/
- Instructions on iClickers can be found here:
  - http://pollinghelp.cit.cornell.edu/iclicker-basics/
  - Find these links on the course webpage
  - Click "Texts/iClickers"
  - Look under "iClickers"

Warm-Up: Using Python

- How do you plan to use Python?

A. I want to work mainly in the ACCEL lab
B. I want to use my own Windows computer
C. I want to use my own Macintosh computer
D. I want to use my own Linux computer
E. I will use whatever I can get my hands on

Type: Set of values and the operations on them

- Type **int**:
  - **Values**: integers
  - **Ops**: +, –, *, //, %, **
- Type **float**:
  - **Values**: real numbers
  - **Ops**: +, –, *, /, **
- Type **bool**:
  - **Values**: **True** and **False**
  - **Ops**: not, and, or
- Type **str**:
  - **Values**: string literals
    - Double quotes: "abc"
    - Single quotes: 'abc'
  - **Ops**: + (concatenation)

Will see more types in a few weeks

Converting Values Between Types

- Basic form: *type*(*value*)
  - `float(2)` converts value 2 to type **float** (value now 2.0)
  - `int(2.6)` converts value 2.6 to type **int** (value now 2)
  - Explicit conversion is also called "casting"
- Narrow to wide: **bool** ⇒ **int** ⇒ **float**
  - *Widening*. Python does automatically if needed
    - **Example**: `1/2.0` evaluates to 0.5 (casts 1 to **float**)
  - *Narrowing*. Python *never* does this automatically
    - Narrowing conversions cause information to be lost
    - **Example**: `float(int(2.6))` evaluates to 2.0

Operator Precedence

- What is the difference between the following?
  - 2*(1+3)
  - 2*1 + 3
- Operations are performed in a set order
  - Parentheses make the order explicit
  - What happens when there are no parentheses?
- **Operator Precedence**: The *fixed* order Python processes operators in *absence* of parentheses

Operator Precedence

- What is the difference between the following?
  - 2*(1+3) **add, then multiply**
  - 2*1 + 3 **multiply, then add**
- Operations are performed in a set order
  - Parentheses make the order explicit
  - What happens when there are no parentheses?
- **Operator Precedence**: The *fixed* order Python processes operators in *absence* of parentheses

Precedence of Python Operators

- **Exponentiation**: **
- **Unary operators**: + –
- **Binary arithmetic**: * / %
- **Binary arithmetic**: + –
- **Comparisons**: < > <= >=
- **Equality relations**: == !=
- **Logical not**
- **Logical and**
- **Logical or**

- Precedence goes downwards
  - Parentheses highest
  - Logical ops lowest
- Same line = same precedence
  - Read "ties" left to right
  - Example: 1/2*3 is (1/2)*3

- Section 2.7 in your text
- See website for more info
- Was major portion of Lab 1

Expressions vs Statements

Expression

- **Represents** something
  - Python *evaluates it*
  - End result is a value
- Examples:
  - `2.3` — Value
  - `(3+5)/4` — Complex Expression

Statement

- **Does** something
  - Python *executes it*
  - Need not result in a value
- Examples:
  - `print('Hello')`
  - `import sys`

Will see later this is not a clear cut separation

Variables (Section 2.1)

- A **variable**
  - is a **named** memory location (**box**)
  - contains a **value** (in the box)
  - can be used in expressions
- Examples:

Variable names must start with a letter (or _).

x	5	Variable **x**, with value 5 (of type **int**)
area	20.1	Variable **area**, w/ value 20.1 (of type **float**)

Variables (Section 2.1)

- A **variable**
  - is a **named** memory location (**box**)
  - contains a **value** (in the box)
  - can be used in expressions
- Examples:

Variable names must start with a letter (or _).

The type belongs to the *value*, not to the *variable*.

x	5	Variable **x**, with value 5 (of type **int**)
area	20.1	Variable **area**, w/ value 20.1 (of type **float**)

Variables (Section 2.1)

- A **variable**
  - is a **named** memory location (**box**)
  - contains a **value** (in the box)
  - can be used in expressions

The value in the box is then used in evaluating the expression.

The type belongs to the *value*, not to the *variable*.

- Examples:

Variable names must start with a letter (or _).

x	5	Variable **x**, with value 5 (of type **int**)
area	20.1	Variable **area**, w/ value 20.1 (of type **float**)

Variables (Section 2.1)

- A **variable**
  - is a **named** memory location (**box**)
  - contains a **value** (in the box)
  - can be used in expressions

The value in the box is then used in evaluating the expression.

The type belongs to the *value*, not to the *variable*.

- Examples:

Variable names must start with a letter (or _).

x	5	Variable **x**, with value 5 (of type **int**)
area	20.1	Variable **area**, w/ value 20.1 (of type **float**)

1e2 is a **float**, but e2 is a variable name

Variables and Assignment Statements

- Variables are created by **assignment statements**
  - Create a new variable name and give it a value

```
x = 5
```

- This is a **statement**, not an **expression**
  - Tells the computer to DO something (not give a value)
  - Typing it into >>> gets no response (but it is working)
- Assignment statements can have expressions in them
  - These expressions can even have variables in them

```
x = x + 2
```

Two steps to execute an assignment:
1. evaluate the expression on the right
2. store the result in the variable on the left

Variables and Assignment Statements

- Variables are created by **assignment statements**
  - Create a new variable name and give it a value

```
x = 5
```

the value

the variable

- This is a **statement**, not an **expression**
  - Tells the computer to DO something (not give a value)
  - Typing it into >>> gets no response (but it is working)
- Assignment statements can have expressions in them
  - These expressions can even have variables in them

```
x = x + 2
```

Two steps to execute an assignment:
1. evaluate the expression on the right
2. store the result in the variable on the left

Variables and Assignment Statements

- Variables are created by **assignment statements**
  - Create a new variable name and give it a value

```
x = 5
```

the value

the variable



- This is a **statement**, not an **expression**
  - Tells the computer to DO something (not give a value)
  - Typing it into >>> gets no response (but it is working)
- Assignment statements can have expressions in them
  - These expressions can even have variables in them

```
x = x + 2
```

Two steps to execute an assignment:
1. evaluate the expression on the right
2. store the result in the variable on the left

Variables and Assignment Statements

- Variables are created by **assignment statements**
  - Create a new variable name and give it a value

```
x = 5
```

the value

the variable

x	5

- This is a **statement**, not an **expression**
  - Tells the computer to DO something (not give a value)
  - Typing it into >>> gets no response (but it is working)
- Assignment statements can have expressions in them
  - These expressions can even have variables in them

```
x = x + 2
```

Two steps to execute an assignment:
1. evaluate the expression on the right
2. store the result in the variable on the left

Variables and Assignment Statements

- Variables are created by **assignment statements**
  - Create a new variable name and give it a value

```
x = 5
```

the value

the variable

x | 5

- This is a **statement**, not an **expression**
  - Tells the computer to DO something (not give a value)
  - Typing it into >>> gets no response (but it is working)
- Assignment statements can have expressions in them
  - These expressions can even have variables in them

```
x = x + 2
```

the expression

the variable

Two steps to execute an assignment:
1. evaluate the expression on the right
2. store the result in the variable on the left

Variables and Assignment Statements

- Variables are created by **assignment statements**

"gets"

Create a new variable name and give it a value

the value

```
x = 5
```

the variable

x | 5

- This is a **statement**, not an **expression**
  - Tells the computer to DO something (not give a value)
  - Typing it into >>> gets no response (but it is working)
- Assignment statements can have expressions in them
  - These expressions can even have variables in them

the expression

```
x = x + 2
```

the variable

Two steps to execute an assignment:
1. evaluate the expression on the right
2. store the result in the variable on the left

Execute the Statement: `x = x + 2`

- Draw variable x on piece of paper:

Execute the Statement: `x = x + 2`

- Draw variable x on piece of paper:

- Step 1: evaluate the expression `x + 2`
  - For x, use the value in variable x
  - Write the expression somewhere on your paper

Execute the Statement: `x = x + 2`

- Draw variable x on piece of paper:

  x | 5 |

- Step 1: evaluate the expression `x + 2`
  - For x, use the value in variable x
  - Write the expression somewhere on your paper
- Step 2: Store the value of the expression in `x`
  - Cross off the old value in the box
  - Write the new value in the box for x

Execute the Statement: `x = x + 2`

- Draw variable x on piece of paper:

  x | 5 |

- Step 1: evaluate the expression `x + 2`
  - For x, use the value in variable x
  - Write the expression somewhere on your paper
- Step 2: Store the value of the expression in `x`
  - Cross off the old value in the box
  - Write the new value in the box for x
- Check to see whether you did the same thing as your neighbor, discuss it if you did something different.

Which One is Closest to Your Answer?

A:

x ~~5~~ 7

B:

x 5

x 7

C:

x ~~5~~

x 7

D:

¯_(ツ)_/¯

Which One is Closest to Your Answer?

A:

x ~~5~~ 7

B:

x 5

x 7

C:

x ~~5~~

x 7

```
x = x + 2
```

Execute the Statement: `x = 3.0 * x + 1.0`

- You have this:



Execute the Statement: `x = 3.0 * x + 1.0`

- You have this:

  x ~~5~~ 7

- Execute this command:
  - Step 1: **Evaluate** the expression `3.0 * x + 1.0`
  - Step 2: **Store** its value in x

Execute the Statement: `x = 3.0 * x + 1.0`

- You have this:

  x | ~~5~~ 7

- Execute this command:
  - Step 1: **Evaluate** the expression `3.0 * x + 1.0`
  - Step 2: **Store** its value in x
- Check to see whether you did the same thing as your neighbor, discuss it if you did something different.

Which One is Closest to Your Answer?

A:

x ~~5~~ ~~7~~ 22.0

B:

x ~~5~~ 7

x 22.0

C:

x ~~5~~ ~~7~~

x 22.0

D:

¯_(ツ)_/¯

Which One is Closest to Your Answer?

A:

x ~~5~~ ~~7~~ 22.0

B:

x ~~5~~ 7

x 22.0

C:

x ~~5~~ ~~7~~

x 22.0

```
x = 3.0 * x + 1.0
```

Execute the Statement: `x = 3.0 * x + 1.0`

- You now have this:

  x | ~~5~~ ~~7~~ 22.0 |

- The command:
  - Step 1: **Evaluate** the expression `3.0 * x + 1.0`
  - Step 2: **Store** its value in x
- This is how you execute an assignment statement
  - Performing it is called **executing the command**
  - Command requires both **evaluate** AND **store** to be correct
  - Important *mental model* for understanding Python

Exercise: Understanding Assignment

- Add another variable, interestRate, to get this:

x	~~5~~ ~~7~~ 22.0	interestRate	4

- Execute this assignment:

```
interestRate = x / interestRate
```

- Check to see whether you did the same thing as your neighbor, discuss it if you did something different.

Which One is Closest to Your Answer?

A:

x ~~5~~ ~~7~~ ~~22.0~~ 5.5

interestRate ~~4~~ 5.5

B:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~

interestRate 5.5

C:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ 5.5

D:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ 5

Which One is Closest to Your Answer?

A:

x ~~5~~ ~~7~~ ~~22.0~~ 5.5

interestRate ~~4~~

B:

x ~~5~~ ~~7~~ 22.0

~~4~~

5.5

C:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ 5.5

interestRate ~~4~~ 5

E:

¯_(ツ)_/¯

Which One is Closest to Your Answer?

```
interestRate = x/interestRate
```

B:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~

interestRate 5.5

C:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ 5.5

D:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ 5

Exercise: Understanding Assignment

- You now have this:

  x | ~~5~~ ~~7~~ 22.0 | interestRate | ~~4~~ 5.5 |

- Execute this assignment:

```
intrestRate =  x + interestRate
```

- Check to see whether you did the same thing as your neighbor, discuss it if you did something different.

Which One is Closest to Your Answer?

A:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ ~~5.5~~ 27.5

B:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ 5.5

intrestRate 27.5

C:

x ~~5~~ ~~7~~ ~~22.0~~ 27.5

interestRate ~~4~~ 5.5

D:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ ~~5.5~~

intrestRate 27.5

Which One is Closest to Your Answer?

A:

x 22.0

interestRate

B:

x 22.0

estRate 5.5

27.5

E:

¯_(ツ)_/¯

C:

x 22.0

interestRate 5.5

interestRate 5.5

intrestRate 27.5

Which One is Closest to Your Answer?

A:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ ~~5.5~~ 27.5

B:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ 5.5

intrestRate 27.5

```
intrestRate =  x + interestRate
```

^
e

Which One is Closest to Your Answer?

A:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ ~~5.5~~ 27.5

B:

x ~~5~~ ~~7~~ 22.0

interestRate ~~4~~ 5.5

intrestRate 27.5

```
intrestRate =  x + interestRate
```

^ e

Spelling mistakes in Python are bad!!

Dynamic Typing

- Python is a **dynamically typed language**
  - Variables can hold values of any type
  - Variables can hold different types at different times
  - Use `type(x)` to find out the type of the value in x
  - Use names of types for conversion, comparison

```
type(x) == int
x = float(x)
type(x) == float
```

- The following is acceptable in Python:

```
>>> x = 1
>>> x = x / 2.0
```

- Alternative is a **statically typed language** (e.g. Java)
  - Each variable restricted to values of just one type

Dynamic Typing

- Python is a **dynamically typed language**
  - Variables can hold values of any type
  - Variables can hold different types at different times
  - Use `type(x)` to find out the type of the value in x
  - Use names of types for conversion, comparison

```
type(x) == int
x = float(x)
type(x) == float
```

- The following is acceptable in Python:

```
>>> x = 1
```
← x contains an **int** value

```
>>> x = x / 2.0
```
← x now contains a **float** value

- Alternative is a **statically typed language** (e.g. Java)
  - Each variable restricted to values of just one type

Dynamic Typing

- Often want to track the type in a variable
  - What is the result of evaluating x / y?
  - Depends on whether x, y are **int** or **float** values
- Use expression `type(<expression>)` to get type
  - `type(2)` evaluates to `<type 'int'>`
  - `type(x)` evaluates to type of contents of x
- Can use in a boolean expression to test type
  - `type('abc') == str` evaluates to **True**