Exponents

Exponential with base a: Domain $= R$, Range$=R^+$

$$f(x) = a^x$$

- Note: a, the *base*, is fixed; x varies
- You probably know: $a^n = a \times \cdots \times a$ (n times)

How do we define $f(x)$ if x is not a positive integer?

- **Want:** (1) $a^{x+y} = a^x a^y$; (2) $a^1 = a$

This means

- $a^2 = a^{1+1} = a^1 a^1 = a \times a$
- $a^3 = a^{2+1} = a^2 a^1 = a \times a \times a$
- ...
- $a^n = a \times \ldots \times a$ (n times)

We get more:

- $a = a^1 = a^{1+0} = a \times a^0$
  - Therefore $a^0 = 1$
- $1 = a^0 = a^{b+(-b)} = a^b \times a^{-b}$
  - Therefore $a^{-b} = 1/a^b$

- $a = a^1 = a^{\frac{1}{2}+\frac{1}{2}} = a^{\frac{1}{2}} \times a^{\frac{1}{2}} = (a^{\frac{1}{2}})^2$
  - Therefore $a^{\frac{1}{2}} = \sqrt{a}$
- Similar arguments show that $a^{\frac{1}{k}} = \sqrt[k]{a}$
- $a^{mx} = a^x \times \cdots \times a^x (m \text{ times}) = (a^x)^m$
  - Thus, $a^{\frac{m}{n}} = (a^{\frac{1}{n}})^m = (\sqrt[n]{a})^m$.

This determines a^x for all x rational. The rest follows by continuity.

Logarithms

Logarithm base a: Domain $= R^+$; Range $= R$

$$y = \log_a(x) \Leftrightarrow a^y = x$$

- $\log_2(8) = 3$; $\log_2(16) = 4$; $3 < \log_2(15) < 4$

The key properties of the log function follow from those for the exponential:

1. $\log_a(1) = 0$ (because $a^0 = 1$)
2. $\log_a(a) = 1$ (because $a^1 = a$)
3. $\log_a(xy) = \log_a(x) + \log_a(y)$

   Proof: Suppose $\log_a(x) = z_1$ and $\log_a(y) = z_2$.

   Then $a^{z_1} = x$ and $a^{z_2} = y$.
   Therefore $xy = a^{z_1} \times a^{z_2} = a^{z_1+z_2}$.
   Thus $\log_a(xy) = z_1 + z_2 = \log_a(x) + \log_a(y)$.
4. $\log_a(x^r) = r \log_a(x)$
5. $\log_a(1/x) = -\log_a(x)$ (because $a^{-y} = 1/a^y$)
6. $\log_b(x) = \log_a(x)/\log_a(b)$

Examples:

- $\log_2(1/4) = -\log_2(4) = -2.$
- $\log_2(-4)$ undefined
- $$\begin{aligned} & \log_2(2^{10}3^5) \\ = \; & \log_2(2^{10}) + \log_2(3^5) \\ = \; & 10\log_2(2) + 5\log_2(3) \\ = \; & 10 + 5\log_2(3) \end{aligned}$$

Limit Properties of the Log Function

$$\lim_{x\to\infty} \log(x) = \infty$$
$$\lim_{x\to\infty} \frac{\log(x)}{x} = 0$$

As x gets large $\log(x)$ grows without bound.

But x grows MUCH faster than $\log(x)$.

In fact, $\lim_{x\to\infty}(\log(x)^m)/x = 0$

Polynomials

$f(x) = a_0 + a_1 x + a_2 x^2 + \cdots + a_k x^k$ is a *polynomial* function.

- $a_0, \ldots, a_k$ are the *coefficients*

You need to know how to multiply polynomials:

$$\begin{aligned} & (2x^3 + 3x)(x^2 + 3x + 1) \\ = \; & 2x^3(x^2 + 3x + 1) + 3x(x^2 + 3x + 1) \\ = \; & 2x^5 + 6x^4 + 2x^3 + 3x^3 + 9x^2 + 3x \\ = \; & 2x^5 + 6x^4 + 5x^3 + 9x^2 + 3x \end{aligned}$$

Exponentials grow MUCH faster than polynomials:

$$\lim_{x \to \infty} \frac{a_0 + \cdots + a_k x^k}{b^x} = 0 \text{ if } b > 1$$

Why Rates of Growth Matter

Suppose you want to design an algorithm to do sorting.

- The naive algorithm takes time $n^2/4$ on average to sort n items
- A more sophisticated algorithm times time $2n\log(n)$

Which is better?

$$\lim_{n\to\infty}(2n\log(n)/(n^2/4)) = \lim_{n\to\infty}(8\log(n)/n) = 0$$

For example,

- if $n = 1,000,000$, $2n\log(n) = 40,000,000$ — this is doable
  $n^2/4 = 250,000,000,000$ — this is not doable

Algorithms that take exponential time are hopeless on large datasets.

Sum and Product Notation

$$\sum_{i=0}^{k} a_i x^i = a_0 + a_1 x + a_2 x^2 + \cdots + a_k x^k$$

$$\sum_{i=2}^{5} i^2 = 2^2 + 3^2 + 4^2 + 5^2 = 54$$

Can limit the set of values taken on by the *index* i:

$$\sum_{\{i:2 \le i \le 8 | i \text{ even}\}} a_i = a_2 + a_4 + a_6 + a_8$$

Can have double sums:

$$\begin{aligned}
& \textstyle\Sigma_{i=1}^{2} \Sigma_{j=0}^{3} a_{ij} \\
= \; & \textstyle\Sigma_{i=1}^{2} \left(\Sigma_{j=0}^{3} a_{ij} \right) \\
= \; & \textstyle\Sigma_{j=0}^{3} a_{1j} + \Sigma_{j=0}^{3} a_{2j} \\
= \; & a_{10} + a_{11} + a_{12} + a_{13} + a_{20} + a_{21} + a_{22} + a_{23}
\end{aligned}$$

Product notation similar:

$$\prod_{i=0}^{k} a_i = a_0 a_1 \cdots a_k$$

Changing the Limits of Summation

This is like changing the limits of integration.

- $\Sigma_{i=1}^{n+1} a_i = \Sigma_{i=0}^{n} a_{i+1} = a_1 + \cdots + a_{n+1}$

Steps:

- Start with $\Sigma_{i=1}^{n+1} a_i$.
- Let $j = i - 1$. Thus, $i = j + 1$.
- Rewrite limits in terms of j: $i = 1 \rightarrow j = 0$; $i = n + 1 \rightarrow j = n$
- Rewrite body in terms of $a_i \rightarrow a_{j+1}$
- Get $\Sigma_{j=0}^{n} a_{j+1}$
- Now replace j by i (j is a dummy variable). Get

$$\sum_{i=0}^{n} a_{i+1}$$

Matrix Algebra

An $m \times n$ *matrix* is a two-dimensional array of numbers, with m rows and n columns:

$$\begin{bmatrix} a_{11} & a_{12} & \cdots & a_{1n} \\ a_{21} & a_{22} & \cdots & a_{2n} \\ \vdots & \vdots & & \vdots \\ a_{m1} & a_{m2} & \cdots & a_{mn} \end{bmatrix}$$

- A $1 \times n$ matrix $[a_1 \ldots a_n]$ is a *row vector*.
- An $m \times 1$ matrix is a *column vector*.

We can add two $m \times n$ matrices:

- If $A = [a_{ij}]$ and $B = [b_{ij}]$ then $A + B = [a_{ij} + b_{ij}]$.

$$\begin{bmatrix} 2 & 3 \\ 5 & 7 \end{bmatrix} + \begin{bmatrix} 3 & 7 \\ 4 & 2 \end{bmatrix} = \begin{bmatrix} 5 & 10 \\ 9 & 9 \end{bmatrix}$$

Another important operation: *transposition*.

- If we transpose an $m \times n$ matrix, we get an $n \times m$ matrix by switching the rows and columns.

$$\begin{bmatrix} 2 & 3 & 9 \\ 5 & 7 & 12 \end{bmatrix}^T = \begin{bmatrix} 2 & 5 \\ 3 & 7 \\ 9 & 12 \end{bmatrix}$$

Matrix Multiplication

Given two vectors $\vec{a} = [a_1, \ldots, a_k]$ and $\vec{b} = [b_1, \ldots, b_k]$, their *inner product* (or *dot product*) is

$$\vec{a} \cdot \vec{b} = \sum_{i=1}^{k} a_i b_i$$

- $[1, 2, 3] \cdot [-2, 4, 6] = (1 \times -2) + (2 \times 4) + (3 \times 6) = 24.$

We can multiply an $n \times m$ matrix $A = [a_{ij}]$ by an $m \times k$ matrix $B = [b_{ij}]$, to get an $n \times k$ matrix $C = [c_{ij}]$:

- $c_{ij} = \Sigma_{r=1}^{m} a_{ir} b_{rj}$
- this is the inner product of the ith row of A with the jth column of B

- $\begin{bmatrix} 2 & 3 & 1 \\ 5 & 7 & 4 \end{bmatrix} \times \begin{bmatrix} 3 & 7 \\ 4 & 2 \\ -1 & -2 \end{bmatrix} = \begin{bmatrix} 17 & 18 \\ 39 & 41 \end{bmatrix}$

$$\begin{aligned}
17 &= (2 \times 3) + (3 \times 4) + (1 \times -1) \\
&= (2, 3, 1) \cdot (3, 4, -1) \\
18 &= (2 \times 7) + (3 \times 2) + (1 \times -2) \\
&= (2, 3, 1) \cdot (7, 2, -2) \\
39 &= (5 \times 3) + (7 \times 4) + (4 \times -1) \\
&= (5, 7, 4) \cdot (3, 4, -1) \\
41 &= (5 \times 7) + (7 \times 2) + (4 \times -2) \\
&= (5, 7, 4) \cdot (7, 2, -2)
\end{aligned}$$

Why is multiplication defined in this strange way?

- Because it's useful!

Suppose

$$\begin{aligned} z_1 &= 2y_1 + 3y_2 + y_3 & y_1 &= 3x_1 + 7x_2 \\ z_2 &= 5y_1 + 7y_2 + 4y_3 & y_2 &= 4x_1 + 2x_2 \\ & & y_3 &= -x_1 - 2x_2 \end{aligned}$$

Thus, $\begin{bmatrix} z_1 \\ z_2 \end{bmatrix} = \begin{bmatrix} 2 & 3 & 1 \\ 5 & 7 & 4 \end{bmatrix} \cdot \begin{bmatrix} y_1 \\ y_2 \\ y_3 \end{bmatrix}$ and $\begin{bmatrix} y_1 \\ y_2 \\ y_3 \end{bmatrix} = \begin{bmatrix} 3 & 7 \\ 4 & 2 \\ -1 & -2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$.

Suppose we want to express the z's in terms of the x's:

$$\begin{aligned} z_1 &= 2y_1 + 3y_2 + y_3 \\ &= 2(3x_1 + 7x_2) + 3(4x_1 + 2x_2) + (-x_1 - 2x_2) \\ &= (2 \times 3 + 3 \times 4 + (-1))x_1 + (2 \times 7 + 3 \times 2 + (-2))x_2 \\ &= 17x_1 + 18x_2 \end{aligned}$$

Similarly, $z_2 = 39x_1 + 41x_2$.

$$\begin{bmatrix} z_1 \\ z_2 \end{bmatrix} = \begin{bmatrix} 2 & 3 & 1 \\ 5 & 7 & 4 \end{bmatrix} \cdot \begin{bmatrix} 3 & 7 \\ 4 & 2 \\ -1 & -2 \end{bmatrix} \cdot \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}.$$

Logic Concepts

The most common mathematical argument is an *implication.*

- *If* $x = 2$ *then* $x^2 = 4$

The implication is sometimes not as obvious:

- $x^2 = 4$ if $x = 2$
- $x^2 = 4$ when $x = 2$
- $x = 2$ implies $x^2 = 4$
- Suppose $x = 2$. Then $x^2 = 4$.
- whenever $x = 2$, $x^2 = 4$
- $x = 2$ only if $x^2 = 4$
- The condition $x = 2$ is sufficient for $x^2 = 4$
- The condition $x^2 = 4$ is necessary for $x = 2$

Note that the order of $x = 2$ and $x^2 = 4$ change.

We denote the implication "If A then B" by

$$A \Rightarrow B$$

YOU NEED TO LEARN TO RECOGNIZE IMPLICATIONS.

Implications chain:

- If $A \Rightarrow B$ and $B \Rightarrow C$ then $A \Rightarrow C$
- $((A \Rightarrow B) \wedge (B \Rightarrow C)) \Rightarrow (A \Rightarrow C)$

The *converse* of $A \Rightarrow B$ is $B \Rightarrow A$.

- *They are not equivalent.*
- $x = 2 \Rightarrow x^2 = 4$ is true; $x^2 = 4 \Rightarrow x = 2$ is not (x could be -2)

The contrapositive of $A \Rightarrow B$ is $\neg\ B \Rightarrow \neg\ A$.

- $\neg$ stands for negation
- A statement is *equivalent* to its contrapositive.
- If $x^2 \neq 4$ then $x \neq 2$.
- If you're asked to prove $A \Rightarrow B$, one way to do it (which is sometimes easier) is to show $\neg B \Rightarrow \neg A$

Equivalence

If both $A \Rightarrow B$ and $B \Rightarrow A$ are true, we write:

$$A \Leftrightarrow B$$

A is *equivalent* to B (A if and only if B; A iff B)

$$(A \Rightarrow B) \Leftrightarrow (\neg B \Rightarrow \neg A)$$

S is a square if and only if S is both a rectangle and a rhombus.

- S being a rectangle and a rhombus is sufficient for S to be a square
- S being a rectangle and a rhombus is necessary for S to be a square

Quantifiers

Quantifiers are words like *every*, *all*, *some*:

- *Every* prime other than two is odd
- *Some* real numbers are not integers

Any is ambiguous: sometimes it means *every*, and sometimes it means *some*

- Anybody knows that $1 + 1 = 2$
- He'd be happy to get an A in any course

Avoid *any*: use every (= all) or some.

Negation

The negation of A, written $\neg A$, is true exactly if A is false:

- The negation of $x = 2$ is $x \neq 2$

Be careful when negating quantifiers!

- What is the negation of A = "Some of John's answers are correct"
- Is it B= "Some of John's answers are not correct"
  - No! A and B can be simultaneously true
- It's "All of John's answers are incorrect".

Algorithms

An *algorithm* is a recipe for solving a problem.

In the book, a particular language is used for describing algorithms.

- You need to learn the language well enough to read the examples
- You need to learn to express your solution to a problem algorithmically and *unambiguously*
- YOU DO NOT NEED TO LEARN IN DETAIL ALL THE IDIOSYNCRACIES OF THE PARTICULAR LANGUAGE USED IN THE BOOK.
  - You will not be tested on it, nor will most of the questions in homework use it

Main Features of the Language

- Assignment statements
  - $x \leftarrow 3$
- **if** ... **then** ... **else** statements
  - **if** $x = 3$ **then** $y \leftarrow y + 1$ **else** $y \leftarrow z$ **endif**
  - $x = 3$ is a *test* or *predicate*; it evaluates to either **true** or **false**
- Selection statement

if B_1 **then** S_1
  B_2 **then** S_2
  $\vdots$
  B_k **then** S_k
  [**else** S_{k+1}]
endif

Iteration

Lots of variants:

repeat until B
  S
endrepeat

or

repeat
  S
endrepeat when B

or

repeat while B
  S
endrepeat

(Same as **while** B **do** S)

or

for $C = 1$ **to** n
  S
endfor

Input and Output

Programs start with input statements of the form:

Input x, a_0, ..., a_k

- the values of the variables $x, a_0, \ldots, a_k$ are assumed to be available at the beginning of the program

Programs end with output statements of the form:

Output P

Example

Input $a_0, a_1, \ldots, a_n, x$

$P \leftarrow a_n$
for $k = 1$ **to** n
    $P \leftarrow Px + a_{n-k}$
Output P

What does this compute?

The Euclidean Algorithm

The *greatest common divisor* of two natural numbers is the largest positive integer that divides both.

- $\gcd(12, 15) = 3$; $\gcd(34, 51) = 17$; $\gcd(6, 45) = 3$
- By convention, $\gcd(n, 0) = n$.

There is a method for calculating the gcd that goes back to Euclid:

- **Key observation:** if $n > m$ and q divides both n and m, then q divides $n - m$ and $n + m$.
  - Proof: If $n = aq$ and $m = bq$ then $n - m = (a - b)q$ and $n + m = (a + b)q$.

Therefore $\gcd(n, m) = \gcd(m, n - m)$.

- Proof: Show that q divides both n and m iff q divides both m and $n - m$. (If q divides n and m, then q divides $n - m$ by the argument above. If q divides m and $n - m$, then q divides $m + (n - m) = n$.
- This allows us to reduce the gcd computation to a simpler case.

We can do even better:

- $\gcd(n, m) = \gcd(m, n - m) = \gcd(m, n - 2m) = \ldots$
- keep going as long as $n - qm \geq 0$ — $\lfloor n/m \rfloor$ steps

Going back to $\gcd(6, 45)$:

- $\lfloor 45/6 \rfloor = 7$; remainder ($45 \bmod 6$) is 3
- $\gcd(6, 45) = \gcd(6, 45 - 7 \times 6) = \gcd(6, 3) = 3$

We can keep this up this procedure to compute $\gcd(n_1, n_2)$:

- If $n_1 \geq n_2$, write n_1 as $q_1 n_2 + r_1$, where $0 \leq r_1 < n_2$
  - $q_1 = \lfloor n_1/n_2 \rfloor$
- $\gcd(n_1, n_2) = \gcd(r_1, n_2)$
- Now $r_1 < n_2$, so switch their roles:
- $n_2 = q_2 r_1 + r_2$, where $0 \leq r_2 < r_1$
- $\gcd(r_1, n_2) = \gcd(r_1, r_2)$
- Notice that $\max(n_1, n_2) > \max(r_1, n_2) > \max(r_1, r_2)$
- Keep going until we have a remainder of 0 (i.e., something of the form $\gcd(r_k, 0)$ or $(\gcd(0, r_k))$
  - This is bound to happen sooner or later

An algorithm for gcd

Input m, n [m, n natural numbers, $m \geq n$]
  $num \leftarrow m$; $denom \leftarrow n$ [Initialize num and $denom$]
  repeat until $denom = 0$
    $q \leftarrow \lfloor num/denom \rfloor$
    $rem \leftarrow num - (q * denom)$ [$rem = num \bmod denom$]
    $num \leftarrow denom$ [New num]
    $denom \leftarrow rem$ [New $denom$; note $num \geq denom$]
  endrepeat
Output num [$num = \gcd(m, n)$]

Example: $\gcd(84, 33)$

Iteration 1: $num = 84$, $denom = 33$, $q = 2$, $rem = 18$
Iteration 2: $num = 33$, $denom = 18$, $q = 1$, $rem = 15$
Iteration 3: $num = 18$, $denom = 15$, $q = 1$, $rem = 3$
Iteration 4: $num = 15$, $denom = 3$, $q = 5$, $rem = 0$
Iteration 5: $num = 3$, $denom = 0 \Rightarrow \gcd(84, 33) = 3$

How do we know this works?

- We have two *loop invariants*, which are true each time we start the loop:
  - $\gcd(m, n) = \gcd(num, denom)$
  - $num \geq denom$
- At the end, $denom = 0$, so $\gcd(num, denom) = num$.

Procedure Calls

It is useful to extend our algorithmic language to have procedures that we can call repeatedly. For example, we may want to have a procedure for computing gcd or factorial, that we can call with different arguments. Here's the notation used in the book:

procedure Name(variable list)
    procedure body (includes a **return** statement)
endpro

- The **return** statement returns control to the portion of the algorithm from where the procedure was called

Example:

procedure Factorial(n)
    $fact \leftarrow 1$
    $m \leftarrow n$
    repeat until $m = 1$
        $fact \leftarrow fact \times m$
        $m \leftarrow m - 1$
    endrepeat
    return $fact$
endpro

Recursion

Recursion occurs when a procedure calls itself.

Example: A recursive procedure for computing gcd

procedure gcd-rec(i, j)
    if $j = 0$ **then** *answer* $\leftarrow i$
        else gcd-rec$(j, i - \lfloor i/j \rfloor j)$
    endif
    return *answer*
endpro
gcd-rec(m, n)

To compute gcd-rec(84,33), we call

- gcd-rec(33,18)
- gcd-rec(18,15)
- gcd-rec(15,3)
- gcd-rec(3,0)

How do we know that the chain of recursive calls is finite?

- Same reasoning as before

Towers of Hanoi

Problem: Move all the rings from pole 1 and pole 2, moving one ring at a time, and never having a larger ring on top of a smaller one.

How do we solve this?

- Think recursively!
- Suppose you could solve it for $n - 1$ rings? How could you do it for n?

Solution

- Move top $n-1$ rings from pole 1 to pole 3 (we can do this by assumption)
  - Pretend largest ring isn't there at all
- Move largest ring from pole 1 to pole 2
- Move top $n-1$ rings from pole 3 to pole 2 (we can do this by assumption)
  - Again, pretend largest ring isn't there

This solution translates to a recursive algorithm:

- Suppose robot($r \to s$) is a command to a robot to move the top ring on pole r to pole s
- Note that if $r, s \in \{1, 2, 3\}$, then $6 - r - s$ is the other number in the set

```
procedure H(n, r, s)        [Move n disks from r to s]
    if n = 1 then robot(r → s)
             else H(n − 1, r, 6 − r − s)
                  robot(r → s)
                  H(n − 1, 6 − r − s, s)
    endif
    return
endpro
```

Tree of Calls

Suppose there are initially three rings on pole 1, which we want to move to pole 2:

Analysis of Algorithms

For a particular algorithm, we want to know:

- How much time it takes
- How much space it takes

What does that mean?

- In general, the time/space will depend on the input size
  - The more items you have to sort, the longer it will take
- Therefore want the answer as a function of the input size
  - What is the best/worst/average case as a function of the input size.

Given an algorithm to solve a problem, may want to know if you can do better.

- What is the *intrinsic complexity* of a problem?

This is what *computational complexity* is about.