

CS5630 Physically Based Realistic Rendering

Steve Marschner
Spring 2026

15 Textures, filtering, and image-based lighting

Overview

Basic sampling problem

- Texture mapping defines a signal in image space
- That signal needs to be filtered: convolved with a filter
- Approximating this drives all the basic algorithms

Antialiasing nonlinear shading

- Basic sampling suffices only if pixel and texture are linearly related
- Normal mapping is the most important nonlinearity

Image based lighting

- Another key application of textures in realistic rendering
- A texture map defines lighting that comes from infinity

Texture mapping from 0 to infinity

When you go close...



Texture mapping from 0 to infinity

When you go far...




Solution: pixel filtering


Problem: Perspective produces very high image frequencies

Solution

- Would like to render textures with one (few) samples/pixel
- Need to filter first!



Solution: pixel filtering



Pixel filtering in texture space

Sampling is happening in image space

- therefore the sampling filter is defined in image space
- sample is a weighted average over a pixel-sized area
- uniform, predictable, friendly problem!


Signal is defined in texture space

- mapping between image and texture is nonuniform
- each sample is a weighted average over a different sized and shaped area
- irregular, unpredictable, unfriendly!

This is a change of variable

- integrate over texture coordinates rather than image coordinates

Pixel footprints



How does area map over distance?

At optimal viewing distance:


- One-to-one mapping between pixel area and texel area

When closer

- Each pixel is a small part of the texel
- magnification
- interpolation is needed

When farther

- Each pixel could include many texels
- “minification”
- averaging is needed



How to get a handle on pixel footprint

We have a nonlinear mapping to deal with


- image position as a function of texture coordinates: $\mathbb{R}^2 \rightarrow \mathbb{R}^2 : \mathbf{u} \mapsto \mathbf{x}(\mathbf{u})$
- but that is too hard

Instead use a local linear approximation

- hinges on the derivative of $\mathbf{u} = (u,v)$ wrt. $\mathbf{x} = (x,y)$


$$\mathbf{u}(\mathbf{x} + \Delta\mathbf{x}) \approx \mathbf{u}(\mathbf{x}) + \frac{\partial \mathbf{u}}{\partial \mathbf{x}} \Delta\mathbf{x}$$

$$\frac{\partial \mathbf{u}}{\partial \mathbf{x}} = \begin{bmatrix} \frac{\partial u}{\partial x} & \frac{\partial u}{\partial y} \\ \frac{\partial v}{\partial x} & \frac{\partial v}{\partial y} \end{bmatrix}$$



Matrix derivative,
or Jacobian

Sizing up the situation with the Jacobian



How to tell minification from magnification

Difference is the size of the derivative

- but what is “size”?
- area: determinant of Jacobian: $\left| \frac{\partial \mathbf{u}}{\partial \mathbf{x}} \right|$
- max-stretch: 2-norm of Jacobian (requires a singular-value computation)
- Frobenius norm of matrix (RMS of 4 entries, easy to compute)
- max dimension of bounding box of quadrilateral footprint: max-abs of 4 entries (conservative)

Take your pick; magnification is when size is more than about 1

Solutions for Minification

For magnification, use a good image interpolation method

- bilinear (usual) or bicubic filter (fancier, smoother) are good picks
- nearest neighbor (box filter) will give you Minecraft-style blockies

For minification, use a good sampling filter to average

- box (simple, though not usually easier)
- gaussian (good choice)

Challenge is to approximate the integral efficiently!

- trilinear interpolation mipmaps — basic and fast
- multi-sample anisotropic filtering (based on mipmap) — popular for real time rendering
- elliptical weighted averaging (based on mipmaps) — popular for offline rendering

Mipmap image pyramid

MIP Maps


- Multum in Parvo: Much in little, many in small places
- Proposed by Lance Williams

Stores pre-filtered versions of texture

- geometric sequence of resolutions (typically factors of 2)

Supports very fast lookup

- but only of circular filters at certain scales



Given derivatives: what is level?

Need to reduce the matrix to a single number

- aka. choosing a matrix norm; several choices available with different tradeoffs
- elementwise max partial derivative:

$$l = \log \left[\max \left(\left| \frac{\partial u}{\partial x} \right|, \left| \frac{\partial v}{\partial x} \right|, \left| \frac{\partial u}{\partial y} \right|, \left| \frac{\partial v}{\partial y} \right| \right) \right]$$

- root-mean-square of partial derivatives:


$$l = \log \sqrt{\left(\frac{\partial u}{\partial x} \right)^2 + \left(\frac{\partial v}{\partial x} \right)^2 + \left(\frac{\partial u}{\partial y} \right)^2 + \left(\frac{\partial v}{\partial y} \right)^2}$$

- either way, you get a non-integer level at which to look up


Using the MIP Map

In level, find texel and

- Return the texture value: point sampling (but still better)!
- Bilinear interpolation
- Trilinear interpolation



Level k



Level $(k + 1)$

Memory Usage

What happens to size of texture?

- level 1 takes $\frac{1}{4}$ the memory of level 0
- level 2 takes $\frac{1}{16}$, etc.
- in total, adds $\frac{1}{3}$ to the storage requirements







image: Kavita Bala


Point sampling




Reference: gaussian
sampling by
512x supersampling



Texture minification
with a trilinear mipmap



Texture minification:
supersampling vs.
trilinear mipmap



EWA filtering (attributed to Greene & Heckbert, but they didn't work out the MIP map part)

Treat pixel as circular

- e.g. Gaussian filter

Use linear apx. for distortion


- circular pixel maps to elliptical footprint
- ellipse dimensions calc'd from quadratic

Loop over texels inside ellipse

- actually over bounding rect
- weight by filter value and accumulate


Select appropriate MIP map level

- so that minor radius is 1–2 texels



Greene & Heckbert '86

Texture minification:
supersampled vs.
EWA



Simpler anisotropic MIP mapping

EWA requires a lot of lookups for diagonally oriented footprints


Instead, approximate your footprint as a single line of blobs

- each blob is produced by taking a single bilinear sample using the standard MIP map


Number of samples proportional to major:minor axis ratio

- with some limit to bound slowness in extreme cases


This is the kind of method used when GPU says it uses “16x anisotropic texture sampling”




BILINEAR



TRILINEAR



ANISOTROPIC



Filtering normal maps

Normal (or bump) maps can produce aliasing too

- shiny surface => color very sensitive to normal
- normal swings around faster as camera moves away => high contrast, high detail image

Filtering the normal map does the wrong thing

- shiny, bumpy surface at a distance becomes a shiny smooth surface
- microfacet theory tells us the non-resolved bumps produce a rough surface appearance

Normal map filtering is about producing appropriate BRDF at large scales

- bumps filtered away, replaced by roughness
- surfaces can become anisotropic depending on normal map content

LEAN Mapping

Linear **E**fficient **A**nisotropic **N**ormal **M**apping

A practical and efficient normal map antialiasing approach


Key ideas:

- Approximate normal mapping as defining a shifted normal distribution function (NDF) (rather than changing the shading frame)

$$e^{-\frac{1}{2} \tilde{h}_b^T \Sigma^{-1} \tilde{h}_b} \quad \rightarrow \quad e^{-\frac{1}{2} (\tilde{h}_n - \tilde{b}_n)^T \Sigma^{-1} (\tilde{h}_n - \tilde{b}_n)}$$


- Use Gaussians for the NDFs
- Approximate the sum of multiple Gaussians by adding the first and second moments

LEAN Mapping




an NDF in tangent-vector space

LEAN Mapping



combining two centered NDFs
in different tangent spaces



combining two off-center NDFs
in a common tangent space

LEAN mapping bottom line [Olano & Baker 2010]

Given normals from a normal map:


$$N = (\vec{b}_n.x, \vec{b}_n.y, \vec{b}_n.z)$$

Store the following in the base level texture:

$$B = (\tilde{b}_n.x, \tilde{b}_n.y) \quad (\tilde{b}_n.x, \tilde{b}_n.y) = (\vec{b}_n.x / \vec{b}_n.z, \vec{b}_n.y / \vec{b}_n.z)$$
$$M = (\tilde{b}_n.x^2, \tilde{b}_n.y^2, \tilde{b}_n.x \tilde{b}_n.y)$$

Allow the textures B and M to be filtered by the MIP map machinery, then at shading time use an NDF defined by the mean B and the covariance:

$$\Sigma = \begin{bmatrix} M.x - B.x * B.x & M.z - B.x * B.y \\ M.z - B.x * B.y & M.y - B.y * B.y \end{bmatrix}$$



LEAN mapping [Olano & Baker I3D 2010]





Figure 13: *Anisotropic bump pattern as a model moves away.*



LEADR mapping [Dupuy et al. SIGGRAPH 2013]

Image-based lighting

Older idea (70s–80s): reflection/environment mapping

- basic technique for rendering shiny surfaces
- originally used in LDR setting

Newer idea (90s–00s): illumination from HDR environment maps

- same idea but the environment is HDR for better accuracy
- HDR environment can also provide lighting: image based lighting (IBL)
- now an indispensable tool in realistic rendering

Refinements (10s–20s)

- various parameterizations
- better sampling methods
- better/faster acquisition methods

Reflection mapping

Early (earliest?) non-decal use of textures

Appearance of shiny objects

- Specular BRDFs produce blurry highlights for glossy surfaces.
- A polished (shiny) object reflects a sharp image of its environment.

The whole key to a shiny-looking material is providing something for it to reflect.



(a)



(b)


Figure 2. (a). A shiny sphere rendered under photographically acquired real-world illumination. (b). The same sphere rendered under illumination by a point light source.

Reflection map

A function from the sphere to colors, stored as a texture.



Spherical environment map



Hand with Reflecting Sphere. M. C. Escher, 1935. lithograph



[CS467 slides]

HDR environment maps and image-based lighting

Older use case: environment map is only for specular reflection

- split BRDF into diffuse and specular
- diffuse part is lit by light sources
- specular part is lit by environment map (with blurring for non-ideal specular)
- efficient but inconsistent
- ideal specular works with LDR environment maps

More accurate and consistent: environment map is part of the illumination

- keep BRDF together, integrate against the incoming illumination from both local sources and the environment map
- simple, works naturally in path tracers
- requires proper HDR environment maps to work correctly

Acquiring HDR environments

Environment maps often come from photos



- just point a camera at a mirror ball
- for better quality, point a camera directly at the environment
- use a wide angle lens and take enough pictures to see everything
- align and stitch the images into a panorama

Problem: camera has a noise floor

- in a sunny scene, the sun is maybe 10k times brighter than a sunlit object (maybe 1M times brighter than a dark corner, or more)
- expose for the scene -> sun is saturated
- expose for the sun -> everything else is lost in the noise

Solution: take several exposures and merge them

Environment Maps



[Paul Debevec]

straight up

straight up

straight up



due East

due South

due West

due North

due East


straight down

straight down



straight down

A spherical panorama, aka. environment map

Cube map



a direction vector maps to the point on the cube that is along that direction.
The cube is textured with 6 square texture maps.




[Zephyris at en.wikipedia]



[Emil Persson]











Sampling directions

Environment map is a continuous function on the sphere

- to get a sampling PDF, convert to a scalar (luminance maybe)

Simple sampling: bag of pixels

- define the radiance as piecewise constant per pixel
- compute the radiance - solid angle product for each pixel
- sample in two steps:
 - select a pixel (discrete choice) with probability proportional to that product
 - select a point uniformly wrt. solid angle in the pixel (continuous choice)
- many methods try to maintain stratification better
- underlying mechanism: selection from a tabulated discrete PDF

