Gorilla: Safe Permissionless Byzantine Consensus

Youer Pu Cornell University

Lorenzo Alvisi Cornell University Ali Farahbakhsh Cornell University

> Ittay Eyal Technion

August 10, 2023

Abstract

Nakamoto's consensus protocol works in a permissionless model and tolerates Byzantine failures, but only offers probabilistic agreement. Recently, the Sandglass protocol has shown such weaker guarantees are not a necessary consequence of a permissionless model; yet, Sandglass only tolerates benign failures, and operates in an unconventional partially synchronous model. We present Gorilla Sandglass, the first Byzantine tolerant consensus protocol to guarantee, in the same synchronous model adopted by Nakamoto, deterministic agreement and termination with probability 1 in a permissionless setting. We prove the correctness of Gorilla by mapping executions that would violate agreement or termination in Gorilla to executions in Sandglass, where we know such violations are impossible. Establishing termination proves particularly interesting, as the mapping requires reasoning about infinite executions and their probabilities.

1 Introduction

Nakamoto's Bitcoin [24] demonstrated that a form of consensus can be reached even if participation is permissionless. Nakamoto achieved this by introducing the cryptographic primitive Proof of Work (PoW) [10, 14] into the common synchronous Byzantine model [9]. With PoW, a process can work for a short while and probabilistically succeed in solving a puzzle. But Bitcoin only achieves a probabilistic notion of consensus: both safety and liveness fail with negligible probability.

Lewis-Pye and Roughgarden showed that deterministic and permissionless consensus cannot be achieved in a synchronous network in the presence of Byzantine failures [19]. Nonetheless, previous work (§2) has achieved deterministic safety and termination with probability 1 under different models. Sandglass [28] assumes a benign model with a non-standard hybrid synchrony model. Momose et al. [23] guarantee termination only if the set of processes stabilizes. Malkhi et al. [21], while leveraging either authenticated channels or digital signatures, propose a solution whose correctness depends on Byzantine nodes comprising fewer than a third of the nodes in the system.

The question is whether it is possible to achieve deterministic safety and termination with probability 1 without limiting either Byzantine behavior or how nodes join and leave, and without relying on authentication.

We answer this question in the affirmative for a synchronous model $(\S3)$ with Byzantine failures. We present Gorilla Sandqlass (or simply Gorilla) $(\S4)$, a consensus protocol that guarantees deterministic safety and termination with probability 1 in this standard model, which we dub GM (for Gorilla Model). Gorilla relies on a form of PoW: Verifiable Delay Functions (VDFs) [6]. We consider an ideal VDF [22] that proves a process waited for a certain amount of time and cannot be amortized. The key difference between a VDF and Nakamoto's PoW is that multiple processes can calculate multiple VDFs concurrently, but cannot, by coordinating, reduce the time to calculate a single VDF. The crux of the protocol is simple. The protocol proceeds in steps. In each step, all (correct) nodes collect VDF solutions from their peers and build new VDFs based on those. Intuitively, correct processes, which are the majority, accrue solutions faster than Byzantine nodes, and progress through the asynchronous rounds of the protocol faster. Eventually, the round inhabited by correct nodes is so far ahead of that occupied by Byzantine nodes that, no longer subject to Byzantine influence, correct nodes can safely decide.

Gorilla Sandglass adopts the general approach of Sandglass [28], in the sense that puzzle results are accrued, with each puzzle built on its predecessors. In Sandglass participants are benign and they send, in each step, a message built on previously received messages. In Gorilla, however, the Byzantine adversary is not limited to acting on step boundaries or communicating at particular times. Surprisingly, Gorilla's correctness can be reduced to the correctness of a variation of Sandglass. We perform this reduction in two steps (§5).

We first show that, for every execution of Gorilla in GM, there is a matching execution where the Byzantine processes adhere to step boundaries, in a model we call GM+. In the mapped execution, Byzantine processes only start calculating their VDF at the beginning of a step and only send messages at the end of a step. GM+ is a purely theoretical device, as it allows operations that cannot be implemented by actual cryptographic primitives. In particular, it allows Byzantine processes to start calculating a VDF in a step s building on any VDF computed by other Byzantine nodes that will be completed by the end of s, rather than by the start s, as allowed by GM (and actually feasible in reality). Nonetheless, GM+ serves as a crucial stepping stone towards proving Gorilla's correctness.

Next, we show that, given an execution in GM+ that violates correctness, there exists a corresponding execution of Sandglass in a model we call SM+. The SM+ model is similar to that of Sandglass: in both, processes are benign and propagation time is bounded for messages among correct processes and unbounded for messages to and from so-called *defective nodes*. But unlike Sandglass, in SM+ a message from a defective node can reference another message generated by another defective node during the same step (similar to how GM+ allows Byzantine nodes to calculate a VDF that builds on VDFs calculated by other Byzantine nodes in the same step).

Together, this pair of reduction steps establishes that if an execution of Gorilla in GM violates correctness with positive probability, then so does an execution of Sandglass in SM+. To conclude Gorilla's proof of correctness, all that is left to show is that Sandglass retains deterministic safety and termination with probability 1 in the SM+ model: fortunately, the correctness proof of Sandglass [28] works almost without change (\S A) in SM+. Thus, a violation of correctness in Gorilla results in a contradiction, and therefore, Gorilla is correct.

Gorilla demonstrates that it is *possible* to achieve deterministic safety and liveness with probability 1 in a permissionless Byzantine model. Yet, possible does not mean *practical*: Gorilla is not, since, like the Sandglass protocol that inspires it, it requires an exponential number of rounds to terminate. By answering the fundamental question of possibility, Gorilla ups the ante: is there a practical solution to deterministically safe permissionless consensus?

2 Related Work

Lewis-Pye et al. [19] have proven that deterministic consensus is impossible in the permissionless setting. Therefore, for at least one of safety and liveness probabilistic guarantees are inevitable. Gorilla concedes little: it manages to keep safety deterministic, and guarantees liveness with probability 1.

Several protocols [3, 4, 7, 11, 12, 17, 25] have embraced Bitcoin's permissionless participation and probabilistic safety. All rely for correctness on probabilistic mechanisms, which leave open the possibility that Byzantine nodes may overturn safety or liveness guarantees with positive probability. Gorilla avoids this peril by basing correctness on the process of accruing a deterministic number of messages.

Few proposals achieve deterministic safety in a permissionless setting [21, 23, 28]. Momose et al. [23] introduce the concept of *eventually stable participation*, akin to partial synchrony; it requires that, after an unknown global stabilization time, for each T-wide time interval [t, t+T], at least half of the nodes ever awake during the interval are correct and do not leave. Gorilla guarantees progress without assuming stability in participation.

Pu et al. [28] propose Sandglass, which achieves deterministic safety but only in a benign setting. Gorilla extends Sandglass to tolerate Byzantine failures.

Malkhi et al. [21] let nodes join and leave at any time, as in Gorilla. Unlike Gorilla, however, they must rely on authenticated channels to tolerate fluctuations in the number of adversaries. Further, Byzantine nodes must be fewer than a third of active nodes, while in Gorilla they must be fewer than one half.

Several works have modeled permissionless participation [2, 18, 27].

Pass et al. [27] introduce the *sleepy participation model*, in which honest nodes are either awake or asleep. Awake nodes participate in the protocol, while asleep nodes neither participate nor relay messages. Byzantine nodes are always awake, but the scheduler can adaptively turn an honest node Byzantine, as long as Byzantine nodes remain a minority of awake nodes. Gorilla similarly assumes that correct and Byzantine nodes can join and leave at any time, as long as a majority of active nodes are correct. Unlike the sleepy model, however, Gorilla requires no public key infrastructure, and, unlike sleepy consensus, guarantees deterministic safety.

Unlike Gorilla, Lewis-Pye et al. [18] do not offer a consensus protocol, but rather focus on introducing *resource pools*, an abstraction that aims to capture resources used to establish identity in permissionless systems, *e.g.*, computational power through PoW and fiscal power through Proof of Stake (PoS).

Aspnes et al. [2] explore consensus in an asynchronous benign model where an unbounded number of nodes can join and leave, but where at least one node is required to live forever, or until termination. Gorilla instead assumes a synchronous model, tolerates Byzantine failures, and allows any node to join and leave, as long as a majority of active nodes is correct.

Verifiable Delay Functions (VDFs) [6] have been leveraged as a resource against Byzantine adversaries in various works [8, 16, 20, 30], specifically to defend PoS systems from attacks where participants can go back in time and mine blocks. Gorilla leverages VDFs to rate-limit the ability of Byzantine nodes to create valid messages.

3 Model

The system is comprised of an infinite set of nodes $\{p_1, p_2, ...\}$. Time progresses in discrete ticks 0, 1, 2, 3, ... In each tick, a subset of the nodes is *active*; the rest are *inactive*. The upper bound on active nodes in any tick, necessary to the safety of Nakamoto's permissionless consensus [26], is \mathcal{N} , and there is at least one active node in every tick. Starting from tick 0, every K ticks are grouped into a step: each step i consists of ticks iK, iK + 1, ..., iK + K - 1.

A Verifiable Delay Function (VDF) is a function whose calculation requires completing a given number of sequential steps. Thus, evaluating a VDF requires the evaluator to spend a certain amount of time in the process. Specifically, we require the evaluation of a single VDF to take K ticks. We refer to the intermediate random values that this evaluation produces at the end of each of the K ticks as the units of the VDF evaluation (or, more succinctly, the units of the VDF). We denote the *i*-th unit of evaluating the VDF of some input γ by vdf_{γ}^{i} ; we denote the final result (*i.e.*, vdf_{γ}^{K}) by vdf_{γ} , or, when there is no ambiguity, by vdf.

We model the calculation of VDFs with the help of an *oracle* Ω . Nodes use Ω both to iteratively obtain the units of a VDF and to verify whether a given value is the *vdf* of a given input. In particular, Ω provides the following API:

 $\operatorname{\mathbf{Get}}(\gamma, vdf_{\gamma}^{i})$: returns $vdf_{\gamma}^{(i+1)}$. By convention, invoking $\operatorname{\mathbf{Get}}(\gamma, \bot)$ returns vdf_{γ}^{1} . The oracle remembers how it responded to a Get query – so that, even though the units of a VDF are random values, identical queries produce identical responses. Ω accepts at most one call to Get() in any tick from each node.

Verify (vdf, γ) : returns True iff $vdf = vdf_{\gamma}^{K}$. Ω accepts any number of calls to Verify() in any tick from any node.

If $\operatorname{Get}(\gamma, \bot)$ is called at tick t and step s, we say the VDF calculation for γ starts at tick t and step s. Similarly, the VDF calculation for γ finishes at tick t and step s if $\operatorname{Get}(\gamma, vdf_{\gamma}^{K-1})$ is called at tick t and step s.

In each tick, an active node receives a non-negative number of messages, updates its variables – potentially including calls to the oracle – and then communicates with others using a synchronous broadcast network. The network allows each active node to broadcast and receive unauthenticated messages. Node p_i invokes $Broadcast_i(m)$ to broadcast a message m, and receives broadcast messages from other nodes (and itself) by invoking $Receive_i$. The network neither generates nor duplicates messages and ensures that if a node receives a message m in tick t, then m is broadcast in tick (t - 1). The network propagation time is negligible compared to a tick, *i.e.*, to the time necessary to calculate a unit of a VDF. By executing the command $Receive_i$, a newly joining node p_i receives all messages broadcast by correct nodes prior to its activation. Nodes whose network connections with other nodes are asynchronous can be modeled as Byzantine, as Byzantine nodes can deliberately or unintentionally delay messages sent from or to them. Therefore, Gorilla also tolerates asynchrony, as long as the nodes that communicate asynchronously are a minority.

Correct nodes do not deviate from their specification and constitute a majority of active nodes at each tick. Correct nodes always join at the beginning of a step and leave when a step ends. Hence, a correct node is active from the first to the last tick of a step. The remaining nodes are *Byzantine* and can suffer from arbitrary failures. Byzantine nodes can join and leave at any tick.

All nodes are initialized with a value $v_i \in \{0, 1\}$ upon joining the system. An active node p_i decides by calling $Decide_i(v)$ for some value v. A protocol solves the consensus problem if it guarantees the following properties [9]:

Definition 1 (Agreement). If a correct node decides a value v, then no correct node decides a value other than v.

Definition 2 (Validity). If all nodes that ever join the system have initial value v and there are no Byzantine nodes, then no correct node decides $v' \neq v$.

Definition 3 (Termination). Every correct node that remains active eventually decides.

4 Gorilla

Gorilla borrows its general structure from Sandglass (see Algorithm 1) [28]. Executions proceed in asynchronous rounds (even though, unlike Sandglass, Gorilla assumes a standard synchronous model of communication between all

nodes). Upon receiving a threshold of valid messages for the current round, nodes progress to the next round; if all the messages received by a correct node propose the same value v for sufficiently many consecutive rounds, the node decides v. The number of active nodes is bounded by \mathcal{N} but otherwise unknown. Within this bound, it can fluctuate arbitrarily, but both safety and liveness depend on the correctness of a majority of nodes.

The key aspects of the protocol can be summarized as follows:

- **Ticks, steps and VDF** Each valid message must contain a vdf. A correct node takes a full step, *i.e.*, K consecutive ticks, to individually calculate a vdf, and at the end of the step sends a valid message that contains the vdf. Byzantine nodes may instead share among themselves the work required to finish the K units of a VDF calculation; even so, it still takes K distinct ticks for Byzantine nodes to compute a vdf. Requiring valid messages to carry a vdf limits Byzantine nodes to sending messages at the same rate as correct nodes; this ensures that, on average across all steps, the correct majority sends at least one more valid message than the minority of nodes that are Byzantine.
- **Choosing a threshold** A node proceeds to round r if it receives at least $\mathcal{T} = \lceil \frac{N^2}{2} \rceil$ messages for round r 1. Even though setting such a threshold does not prevent Byzantine nodes from advancing from round to round, it nonetheless gives the correct nodes an edge in the pace of such progress, since they constitute a majority.
- **Exchanging messages** In each step of the protocol, a node in any round r based on the messages it has received so far searches for the largest round $r_{max} \ge r$ for which it has accrued \mathcal{T} messages. It then broadcasts a message for the next round. The message includes the node's current proposed value v, the vdf, and four other attributes discussed below: the message's *coffer*, a nonce, as well as v's *priority* and *unanimity counter*.
- **Keeping history** Nodes can join the system at any time. To help a joining node catch up, every message broadcast by a node p in round r includes a message coffer that contains: (i) messages from round r 1 received by p to advance to round r; (ii) recursively, messages included in those messages' coffers; and (iii) messages received by p for round r.
- Nonce By making it possible to distinguish between messages that are generated from the same coffer, nonces allow correct nodes to broadcast multiple valid messages during a round while, at the same time, preventing Byzantine nodes from reusing the same vdf to send multiple valid messages based on a given message coffer.
- **Priority and unanimity counter** If a node p only receives the value v from a majority for a sufficient number of consecutive rounds, it decides v. To guarantee the safety of this decision, p assigns a *priority* to the value v that it proposes. This priority is incremented once v is unanimously proposed

for a long stretch of consecutive rounds. To record the length of this stretch, each node computes it upon entering a round r, and includes it as the *unanimity counter* in the messages it sends for round r. If a node collects more than one value in a round r, it chooses the one with the highest priority, and proposes it for round r + 1. In case of a tie, it uses vdf as a source of randomness to choose one of the values randomly. Since vdf is a random number calculated based on the message coffer and a nonce (lines 13-15), a Byzantine node is unable to deliberately pick an input to VDF to deterministically get the desired value.

Message internal consistency and validity A message m is internally consistent if the attributes carried by m can be generated by following Gorilla correctly based on the message coffer carried in m. We denote the vdf in m by vdf_m .

A message m is valid (and thus isValid(m) returns true), if (i) vdf_m can be verified by the message coffer and the nonce of m; (ii) m is internally consistent; and (iii) for any message m' in m's coffer, m' is also valid. Otherwise, m is invalid.

In addition to demonstrating variable initialization, Algorithm 1 presents the algorithm each node p_i runs at each step. Each node p_i starts every step by adding all valid messages, in addition to the messages in their coffers, to the set Rec_i (lines 4-6).

Iterating over Rec_i , node p_i computes the largest round r_{max} for which it has received at least \mathcal{T} messages, and updates its current round to $r_{max} + 1$ (line 8) if the condition in line 7 holds. Once in a new round, p_i does the following: (i) resets its message coffer M and adds to it the messages it has received from the previous round – alongside the messages in *their* coffers (lines 9-11); (ii) picks a nonce and calculates a vdf based on its coffer and the nonce (lines 13-15); (*iii*) chooses its proposal value (lines 16 -20); it chooses the proposal with the highest priority among the previous round messages in its coffer; in case of a tie, it chooses a random number utilizing the randomness in vdf; (iv) determines the priority and the unanimity counter for the messages it will broadcast in the current round (lines 21-25); and finally (v) the node decides v if v's priority is high enough (lines 26-27). If p_i does not enter a new round, it starts to create a message nonetheless: it adds to the message's coffer all messages received for the current round (line 29), and calculates a vdf with the new message coffer and a different nonce as the input (lines 30-32), so that the message is unique. Regardless of whether it enters a round or not, p_i ends every step by broadcasting the message it has created (line 33).

4.1 Comparing Sandglass and Gorilla

Gorilla retains the structure of Sandglass, adding the requirement that valid messages must include a vdf and a nonce. The differences between the protocols are highlighted in orange in Algorithm 1: (i) vdf is calculated for each message

Algorithm 1 Gorilla: Code for node p_i . The orange text highlights where Gorilla departs from Sandglass.

```
1: procedure INIT(input_i)
            v_i \leftarrow input_i; priority<sub>i</sub> \leftarrow 0; uCounter<sub>i</sub> \leftarrow 0; r_i = 1; M_i = \emptyset; Rec<sub>i</sub> = \emptyset;
 2:
     procedure STEP
 3:
           for all m = (\cdot, \cdot, \cdot, \cdot, \cdot, M) received by p_i do
 4:
                if isValid(m) then
 5:
                     Rec_i \leftarrow Rec_i \cup \{m\} \cup M
 6:
 7:
           if \max_{|Rec_i(r)| \geq \mathcal{T}}(r) \geq r_i then
                r_i = \max_{|Rec_i(r)| \ge \mathcal{T}}(r) + 1
 8:
                M_i = \emptyset
 9:
                for all m = (\cdot, r_i - 1, \cdot, \cdot, \cdot, M) \in Rec_i(r_i - 1) do
10:
                     M_i \leftarrow M_i \cup \{m\} \cup M
11:
                M_i \leftarrow M_i \cup Rec_i(r_i)
12:
                vdf \leftarrow \bot; nonce \leftarrow a new arbitrary value
13:
                for j : 1..k do
14:
                     vdf \leftarrow Get((M_i, nonce), vdf)
15:
                Let C be the multi-set of messages in M_i(r_i - 1) with the largest
16:
      priority.
17:
                if all messages in C have the same value v then
                     v_i \leftarrow v
18:
                else
19:
                     v_i \leftarrow vdf \mod 2
20:
                if all messages in M_i(r_i - 1) have the same value v_i then
21:
                     uCounter_i \leftarrow 1 + \min\{uCounter|(\cdot, r_i - 1, v_i, \cdot, uCounter, \cdot) \in
22:
      M_i(r_i - 1)
                else
23:
                     uCounter_i \leftarrow 0
24:
                \begin{array}{l} priority_i \leftarrow \max(0, \left\lfloor \frac{uCounter_i}{\mathcal{T}} \right\rfloor - 5) \\ \textbf{if } priority_i \geq 6\mathcal{T} + 4 \textbf{ then} \end{array}
25:
26:
                     \text{Decide}_i(v_i)
27:
           else
28:
                M_i \leftarrow M_i \cup Rec_i(r_i)
29:
                vdf \leftarrow \bot; nonce \leftarrow a new arbitrary value
30:
                for j : 1..k do
                     vdf = Get((M_i, nonce), vdf)
32:
           broadcast (r_i, v_i, priority_i, uCounter_i, M_i, nonce, vdf)
33:
```

sent (lines 13-15,30-32), (ii) received messages are checked to see if they are valid (line 5); (iii) vdf is used as the source of randomness (line 20) where the protocol requires choosing a value randomly.

These additions are critical to handling Byzantine faults. Both Gorilla and Sandglass rely on correct (respectively, good) nodes sending the majority of unique messages during an execution. In Sandglass, where defective nodes are benign, this property simply follows from requiring correct nodes to be a majority in each step; not so in Gorilla, where faulty nodes can be Byzantine. Requiring valid message in Gorilla to carry a *vdf* preserves correctness by effectively rate-limiting Byzantine nodes' ability to create valid messages.

Given their differences in both failure model and timing assumptions, it is perhaps surprising that so little needs to change when moving from Sandglass to Gorilla. After all, Sandglass assumes a model where failures are benign and a hybrid synchronous model of communication [29]; Gorilla instead assumes a Byzantine failure model, and a synchronous network model (§3). Note, however, that although Sandglass assumes benign failures, its hybrid communication model implicitly accounts for Byzantine nodes strategically choosing the timing for receiving and sending messages to correct nodes: Gorilla can then simply inherit from Sandglass the mechanisms for tolerating such behaviors.

5 Correctness

Despite the similarlity between the Gorilla and Sandglass protocols, proving Gorilla's correctness directly is challenging. Unlike Sandglass, Byzantine nodes can act between step boundaries, interleave VDF computations instead of producing one VDF (and hence one message) at the time, etc. To overcome this complexity, our approach is to leverage as much as possible Sandglass's proof of correctness.

Our battle plan was to first map executions of Gorilla to executions of Sandglass. Then we intended to proceed by contradiction: assume that a correctness guarantee is violated in Gorilla, and map this violation to Sandglass; since correctness violations are not possible in Sandglass [28], we could then conclude that neither they can be in Gorilla.

The best laid plans often go awry, and, as we discuss below, ours was no exception—but we were able to nonetheless retain the conceptual simplicity of our initial approach.

5.1 The Main Story, and How it Fails

The mapping from Gorilla to Sandglass must satisfy certain *well-formedness* and *equivalence* conditions. The former specify how to map a Gorilla execution into one that satisfies the Sandglass model (SM) and follows the Sandglass protocol; the latter allow us to map violations from Gorilla to Sandglass, *i.e.*, they preserve certain properties of the behavior of *correct* nodes in Gorilla and reinterpret them as the behavior of *good* nodes in Sandglass.

Well-formedness requires mapping correct nodes to good nodes, and Byzantine nodes to defective nodes, while respecting model constraints (*e.g.*, at each step defective nodes should be fewer than good nodes). The first half of this mapping is easy: except for calculating a VDF, correct nodes in GM are not doing anything different than good nodes in SM. Thus, mapping a step in GM




Figure 1: An execution that cannot be reorganized in GM (a), and how peeking solves the problem in GM+ (b).

to a step in SM yields a straightforward connection between correct and good nodes. The second half, however, is trickier. Defective nodes in SM can suffer from benign faults like omission and crashing, but these fall short of fully capturing Byzantine behavior in GM. In particular, Byzantine nodes, even when sending valid messages, can violate the timing constraints that Gorilla places on a node's actions, *e.g.*, by splitting the calculation of a single VDF into multiple steps. Thus, before a Gorilla execution can be mapped to a Sandglass execution, Byzantine nodes' actions must be brought to conform to step boundaries and not spill across steps. After tidying things up this way, it must become possible to map the faulty actions of the Byzantine nodes to a combination of crashes, omissions, and network delays, *i.e.*, to the faults and anomalies that SM allows.

Equivalence in turn requires that, when mapping executions from Gorilla to Sandglass, a correct node and its corresponding good node send and receive in every step messages that allow them to update their proposed value, round number, priority, and unanimity counter in the same way. Since messages play the same role in both protocols, this is sufficient for good nodes in Sandglass to decide identically to the corresponding correct nodes in Gorilla.

Our plan to realize this logical mapping involved splitting it into two concrete, intermediate mappings: a first mapping from an initial Gorilla execution to an intermediate Gorilla execution in which Byzantine actions conform to step boundaries; and a second mapping from that intermediate execution to a Sandglass execution. We require all of our well-formedness and equivalence conditions to hold throughout these mappings: (i) model constraints must be always respected, (ii) correct nodes in the intermediate execution send and receive the equivalent (indeed, the same!) messages as their counterparts in the initial execution, at the same steps, and (iii) good nodes in the final execution send and receive equivalent messages as their correct counterparts in the intermediate execution, at the same steps.

Unfortunately, well-formedness and equivalence cannot be satisfied by the first mapping. To see why, consider Figure 1a. Here, each square represents a VDF unit calculated by a Byzantine node for a specific input, denoted by a unique color. Numbered circles represent the corresponding messages, e.g., the VDF units containing (1) are associated with message (1). Each VDF calculation takes three ticks, and a step comprises three ticks. The numbered dashed lines

indicate the steps, *i.e.*, the three ticks between lines i and i + 1 belong to step i. Assume that, to maintain a majority of correct nodes in the system, the maximum allowable number of Byzantine nodes in the four steps shown in the figure are, respectively, 1, 1, 3, and 1. Moreover, assume that messages (4), (5), and (6) all include in their coffers messages (1), (2), and (3). Finally, assume that messages (4), (5), and (6) are sent to correct nodes at the start of Step 4. Since the actions of Byzantine nodes in Figure 1a do not conform to step boundaries, the first mapping should be able to organize them in a way that ensures that (i) correct nodes receive messages (4), (5), and (6) at the beginning of Step 4, and (ii) each of these messages in turn includes messages (1), (2), and (3). Thus, the calculation of the VDFs for messages (1), (2), and (3) must be completed before those for (4), (5), and (6) can start. Now, since steps 0 and 1 include only one Byzantine node, they can only accommodate one VDF, *i.e.*, only one VDF can be calculated in each of steps 0 and 1. Without loss of generality, let those VDFs be (1) and (3), respectively. VDF (2) must still complete before messages (4), (5), and (6): thus, it has to be placed in Step 2. Note that, although Step 2 could accommodate two more Byzantine VDFs at Step 2, they cannot be placed there, since the completion of VDF (2) must precede the start of the calculation of VDFs (4), (5), and (6): the earliest step where they can start is Step 3. However, it is impossible to accommodate all three there, since in Step 3 there is a single Byzantine node.

Our first attempt at mapping executions from Gorilla to Sandglass has thus failed. Fortunately, though, it is possible to retain the strategy that underlies it and overcome the above counterexample without weakening our well-formedness and equivalence conditions. Instead, we proceed to weaken the model in which we operate, by giving Byzantine nodes extra power.

5.2 A New Beginning

Definition 4. Consider an execution η_G in GM and an execution η_G^+ in GM+. We say η_G and η_G^+ are equivalent iff the following conditions are satisfied:

- **Reorg-1** For every correct node p in η_G , there exists a correct node p^+ in η_G^+ , such that p and p^+ (i) join and leave the system at the same ticks in the same steps and (ii) receive and send the same messages at the same ticks in the same steps.
- **Reorg**-2 Each Byzantine node in η_G^+ (i) joins at the first tick of a step and leaves after the last tick of that step; (ii) receives messages at the first tick of a step and sends messages at the last tick of that step; and (iii) sends and receives only valid messages.
- **Reorg-3** If in η_G a Byzantine node sends a valid message m at a tick in step s, then in η_G^+ a Byzantine node sends m at a tick in some step $s' \leq s$.

Lemma 1. There exists a mapping REORG that maps an execution η_G in GM to an execution η_G^+ in GM+, denoted $\eta_G^+ = \text{REORG}(\eta_G)$, such that η_G is equivalent to η_G^+ .

While peeking solves the challenge with reorganizing Byzantine behavior, it complicates our second mapping. The ability to peek granted to Byzantine nodes in GM+ has no equivalent in Sandglass – it simply cannot be reduced to the effects of network delays or to the behavior of defective nodes. Therefore, we weaken SM so that defective nodes can benefit from a capability equivalent to peeking.

We do so by introducing SM+, an extension of SM that is identical to SM, except for the following change: defective nodes at step s can receive any message m sent by a defective node no later than s – as opposed to (s - 1) in SM – as long as m does not contain in its coffer a message that is sent at s. Note that allowing defective nodes to receive in a given step a message m sent by defective nodes within that very step maps to allowing Byzantine nodes to peek at a message whose vdf will be finished by Byzantine nodes within the same step; and the constraint that m shouldn't contain in its coffer other messages sent in the same step, maps to the constraint that Byzantine nodes cannot peek at messages whose coffer also contains a peek result from the same step.

One might rightfully ask: was not the plan to leverage the correctness of Sandglass in SM? Indeed, but fortunately, Sandglass still guarantees deterministic agreement and termination with probability 1 under the SM+ model (§A.3). Thus, it is suitable to map a Gorilla execution in GM+ to a Sandglass execution in SM+, and orient our proof by contradiction with respect to the correctness of Sandglass in SM+.

Formally, we specify our second mapping as follows.

Definition 5. Given a message m in the Gorilla protocol, the mapping MAPM produces a message in the Sandglass protocol as follows

- 1. Omit the vdf and the nonce from m.
- 2. Let p_i be the node that sends m. Include p_i as a field in m.
- 3. If m is the j-th message sent by p_i , add a field uid = j to m.
- 4. Repeat the steps above for all of the messages in m's coffer.

Denote the result by $\hat{m} = MAPM(m)$. We say m and \hat{m} are equivalent. Furthermore, with a slight abuse of notation, we apply MAPM to a set of messages as well, i.e., if \mathcal{M} is a set of messages, and we map each message $m \in \mathcal{M}$, we obtain the message set MAPM(\mathcal{M}).

Definition 6. Consider an execution η_G^+ in GM^+ and an execution η_S^+ in SM^+ . We say η_G^+ and η_S^+ are equivalent iff the following conditions are satisfied:

1. The nodes in η_G^+ are in a one-to-one correspondence with the nodes in η_S^+ . For every node p in η_G^+ , we denote the corresponding node in η_S^+ with \hat{p} .

- 2. Nodes p and \hat{p} join and leave at the same steps in η_G^+ and η_S^+ , respectively. Furthermore, their initial values are the same.
- If p is a Byzantine node, then p̂ is defective in SM+; otherwise, p̂ is a good node in SM+.
- 4. \hat{p} sends \hat{m} at step s in η_S^+ , iff p generates a message m in η_G^+ at step s. Note that in η_G^+ , correct nodes send their messages to all as soon as they are generated, while Byzantine nodes may only send their messages to a subset of nodes once their messages are generated.
- 5. \hat{p} receives \hat{m} at step s in η_S^+ , iff p receives m at step s in η_G^+ .

Lemma 2. Consider any execution η_G in GM, and an execution η_G^+ in GM+ equivalent to η_G . There exists a mapping INTERPRET that maps η_G^+ to an execution η_S^+ in SM+, denoted as $\eta_S^+ = \text{INTERPRET}(\eta_G^+)$, such that η_S^+ is equivalent to η_G^+ .

Finally, for our proof by contradiction to work, we have to show that Sandglass is correct in SM+. The proof is deferred to §A.3.

Theorem 1. Sandglass satisfies agreement and validity deterministically and termination with probability 1 in SM+.

5.2.1 Safety

We prove that Gorilla satisfies Validity and Agreement. The proofs follow the same pattern: assume a violation exists in some execution η_G of Gorilla running in GM; map that execution to $\eta_G^+ = \text{ReoRG}(\eta_G)$ in GM+; then, map η_G^+ again to $\eta_S^+ = \text{ReoRG}(\eta_G^+)$ in SM+; and, finally, rely on the fact that these mappings ensure that correct nodes in η_G and good nodes in η_S^+ reach the same decisions in the same steps to drive a contradiction. This approach is made rigorous in following lemmas, proved in §B.2.

Lemma 3. Consider an arbitrary Gorilla execution η_G , and $\eta_G^+ = \text{REORG}(\eta_G)$. If a correct node p decides a value v at step s in η_G , then p's corresponding node p^+ decides v at step s in η_G^+ .

Lemma 4. Consider any execution η_G in GM. If an execution $\eta_G^+ = \text{REORG}(\eta_G)$ in GM_+ and an execution η_S^+ in SM_+ are equivalent, then the following statements hold:

- 1. If a correct node p decides a value v at step s in η_G^+ , then \hat{p} decides v at step s in η_S^+ .
- 2. Consider the first message m = (r, v, priority, uCounter, M, nonce, vdf)that p generates for round r. Let the step when m is generated be s. If uCounter is 0, then \hat{p} randomly chooses value v as the proposal value at step s in η_S^+ .

We can now state and prove the safety guarantees.

Theorem 2. Gorilla satisfies agreement in GM.

Proof. By contradiction, assume that there exists a Gorilla execution η_G in GM that violates agreement. This means that there exist two correct nodes p_1 and p_2 , two steps s_1 and s_2 , and two values $v_1 \neq v_2$ such that p_1 decides v_1 at s_1 and p_2 decides v_2 at s_2 . Consider $\eta_G^+ = \text{REORG}(\eta_G)$. According to Lemma 3, p_1^+ decides v_1 at s_1 and p_2^+ decides v_2 at s_2 , in η_G^+ . Now, consider $\eta_S^+ = \text{INTERPRET}(\eta_G^+)$. According to Lemma 4, \hat{p}_1^+ decides v_1 at s_1 and \hat{p}_2^+ decides v_2 at s_2 , in η_S^+ . However, this contradicts the fact Sandglass satisfies agreement in SM+ (Theorem 1). Therefore, Gorilla satisfies agreement in GM.

Theorem 3. Gorilla satisfies validity in GM.

Proof. By contradiction, assume that there exists a Gorilla execution η_G , such that (i) all nodes that ever join the system have initial value v; (ii) there are no Byzantine nodes; and (iii) a correct node p decides $v' \neq v$.

Since GM+ is an extension of GM, η_G conforms to GM+. According to Definition 4, $\eta_G^+ = \eta_G$ in GM+ is trivially equivalent to η_G . Consider $\eta_S^+ =$ INTERPRET (η_G^+) .

By the construction of the INTERPRET mapping (in Lemma 2), good nodes in η_S^+ have the same initial values as their corresponding correct nodes in η_G . Furthermore, since there are no Byzantine nodes in η_G^+ , there are no defective nodes in η_S^+ by Definition 6. Therefore, by Validity of Sandglass in SM+ (Theorem 1), no good node decides $v' \neq v$. However, by Lemma 3 and Lemma 4, pdecides $v' \neq v$, which leads to a contradiction. Therefore, Gorilla satisfies validity in GM.

5.3 Liveness

Similar to the safety proof, the liveness proof proceeds by contradiction: it starts with a liveness violation in Gorilla, and maps it to a liveness violation in Sandglass.

Formalizing the notion of violating termination with probability 1 requires specifying the probability distribution used to characterize the probability of termination. To do so, we first have to fix all sources of non-determinism [1, 5, 15]. For our purposes, non-determinism in GM and GM+ stems from correct nodes, Byzantine nodes and their behavior; in SM+, it stems from good nodes, defective nodes and the scheduler.

For correct, good, and defective nodes, non-determinism arises from the joining/leaving schedule and the initial value of each joining node. For Byzantine nodes in GM and GM+, fixing non-determinism means fixing their action *strategy* according to the current history of an execution. Similarly, fixing the scheduler's non-determinism means specifying the timing of message deliveries and the occurrence of benign failures, based on the current history. We, therefore, define non-determinism formally in terms of an environment and a strategy.

To this end, we introduce the notion of a *message history*, and define what it means for a set of messages exchanged in a given step to be *compatible* with the message history that precedes them.

Definition 7. For any given execution in GM and GM+ (resp., SM+), and any step s, the message history up to s, \mathcal{MH}_s , is the set of $\langle m, p, s' \rangle$ triples such that p is a correct node (resp., good node) and p receives m at $s' \leq s$.

Definition 8. We say a set \mathcal{MP}_{s+1} of $\langle m, p, s+1 \rangle$ triples is compatible with a message history up to s, \mathcal{MH}_s , if there exists an execution such that for any $\langle m, p, s+1 \rangle \in \mathcal{MP}_{s+1}$, the correct node (resp., good node) p receives m at step (s+1).

Definition 9. An environment \mathcal{E} in GM and GM+ (resp., SM+) is a fixed joining/leaving schedule and fixed initial value schedule for correct nodes (resp., good and defective nodes).

Definition 10. Given an environment \mathcal{E} , a strategy $\Theta_{\mathcal{E}}$ for the Byzantine nodes (resp., scheduler) in GM and GM+ (resp., SM+) is a function that takes the message history \mathcal{MH}_s up to a given step s as the input, and outputs a set \mathcal{MP}_{s+1} that is compatible with \mathcal{MH}_s .

Before proceeding, there is one additional point to address. The most general way of eliminating non-determinism is to introduce randomness through a fixed probability distribution over the available options. However, the following lemma, proved in §B.3, establishes that Byzantine nodes do not benefit from employing such a randomized strategy.

Lemma 5. For any environment \mathcal{E} , if there exists a randomized Byzantine strategy for Gorilla that achieves a positive non-termination probability, then there exists a deterministic Byzantine strategy for Gorilla that achieves a positive non-termination probability.

Since the output vdf of a call to the VDF oracle is a random number, the (vdf mod 2) operation in line 20 of Gorilla is equivalent to tossing an unbiased coin. Given a strategy $\Theta_{\mathcal{E}}$,¹ the nodes might observe different coin tosses as the execution proceeds; thus, the strategy specifies the action of the Byzantine nodes for all possible coin toss outcomes. The scheduler's strategy in SM+ is similarly specified for all coin toss outcomes. Therefore, once a strategy is determined, it admits a *set* of different executions based on the coin toss outcomes; we denote

 $^{^1\}mathrm{When}$ it is clear from the context, we will omit the environment from the subscript of the strategy.

it by H_{Θ} . Specifically, a strategy determines an action for each outcome of any coin toss.

Given a strategy Θ , we can define a probability distribution $P_{H_{\Theta}}$ over H_{Θ} . For each execution $\eta \in H_{\Theta}$, there exists a unique string of zeros and ones, representing the coin tosses observed during η . Denote this bijective correspondence by COINS : $H_{\Theta} \to \{0,1\}^* \cup \{0,1\}^{\infty}$, and the probability distribution on the coin toss strings in COINS (H_{Θ}) by $\tilde{P}_{H_{\Theta}}$. For every event $E \subset H_{\Theta}$, if COINS(E) is measurable in COINS (H_{Θ}) , then $\tilde{P}_{H_{\Theta}}(\text{COINS}(E))$ is well-defined; thus, $P_{H_{\Theta}}(E)$ is also well-defined and $P_{H_{\Theta}}(E) = \tilde{P}_{H_{\Theta}}(\text{COINS}(E))$. We denote $P_{H_{\Theta}}$ as the probability distribution induced over H_{Θ} by its coin tosses.

Equipped with these definitions, we can formally define termination with probability 1.

Definition 11. The Gorilla protocol terminates with probability 1 iff for every environment \mathcal{E} and every Byzantine strategy Θ based on \mathcal{E} , the probability of the termination event T in H_{Θ} , i.e., $P_{H_{\Theta}}(T)$, is equal to 1.

This definition gives us the recipe for proving by contradiction that Gorilla terminates with probability 1. We first assume there exists a Byzantine strategy Θ that achieves a non-zero non-termination probability, and map this strategy through the REORG and INTERPRET mappings to a scheduler strategy Λ that achieves a non-zero non-termination probability in SM+. However, Λ cannot exist, as the Sandglass protocol terminates with probability 1 in SM+ (Theorem 1).

Lemma 6. If there exists an environment \mathcal{E} and a Byzantine strategy $\Theta_{\mathcal{E}}$ in GM that achieves a positive non-termination probability, then there exists an environment \mathcal{E}' and a Byzantine strategy $\Psi_{\mathcal{E}'}$ in GM+ that also achieves a positive non-termination probability.

Proof. Assume there exist an environment \mathcal{E} and a Byzantine strategy $\Theta_{\mathcal{E}}$ in GM that achieves a positive non-termination probability. Consider the REORG mapping. Since, according to Lemma 1, the joining/leaving and initial value schedules for correct nodes remain untouched by the REORG mapping, we just set $\mathcal{E}' = \mathcal{E}$. In the rest of the proof, we omit the environments for brevity.

We now show that the strategy Ψ exists, and is in fact the same as Θ . For brevity, let R_{Θ} denote $\operatorname{REORG}(H_{\Theta})$, and consider any execution η in H_{Θ} . By Lemma 1, correct nodes in η receive the same messages, at the same steps, as the correct nodes in $\operatorname{REORG}(\eta)$ and, moreover, the coin results in η are exactly the same as the ones in $\operatorname{REORG}(\eta)$. Thus, the message history of correct nodes up to any step s in η is the same as the message history of correct nodes up to the same step in $\operatorname{REORG}(\eta)$. In addition, because $\operatorname{REORG}(\eta)$ is a GM+ execution, compatibility is trivially satisfied. Thus, we conclude that Byzantine nodes in R_{Θ} follow the same strategy as in Θ , conforming to the same coin toss process. Let us denote this strategy with Ψ .

Note that according to Lemma 3, whenever a correct node decides at some step s in η , its corresponding correct node in $\text{Reorg}(\eta)$ decides the same value

at the same step. Therefore, the set of non-terminating executions in H_{Θ} are mapped to the set of non-terminating executions in R_{Θ} in a bijective manner. Let us denote these sets as NT_H and NT_R , respectively. Since the same coin toss process induces probability distributions $P_{H_{\Theta}}$ and $P_{R_{\Theta}}$ on H_{Θ} and R_{Θ} , respectively, we conclude that $P_{H_{\Theta}}(NT_H) = P_{R_{\Theta}}(NT_R)$. Therefore, since $P_{H_{\Theta}}(NT_H) > 0$ by assumption, this concludes our proof, as we have shown the existence of a strategy Ψ in GM+ that achieves a positive non-termination probability.

A similar lemma applies to the second mapping. We prove it in §B.3.

Lemma 7. If there exists an environment \mathcal{E} and a strategy Ψ for Byzantine nodes in GM+ that achieves a positive non-termination probability, then there exists an environment \mathcal{E}' and a scheduler strategy $\Lambda_{\mathcal{E}'}$ in SM+ that also achieves a positive non-termination probability.

Based on these lemmas, we are finally ready to prove Gorilla's liveness guarantee.

Theorem 4. The Gorilla protocol terminates with probability 1.

Proof. By contradiction, assume that there exist a GM environment and a Byzantine strategy Θ in Gorilla that achieve a positive non-termination probability. By Lemma 6, there exist a GM+ environment and a strategy Ψ for the Byzantine nodes in GM+ that achieve a positive non-termination probability. Similarly, by Lemma 7, there exists an SM+ environment and a scheduler strategy Λ in SM+ that achieve a positive non-termination probability. But this is a contradiction, since Sandglass terminates with probability 1 in SM+ (Theorem 1). Thus, Byzantine strategy Θ cannot force a positive non-termination probability; Gorilla terminates with probability 1.

6 Conclusion

Gorilla Sandglass is the first Byzantine-tolerant consensus protocol to guarantee, in the same synchronous model adopted by Nakamoto, deterministic agreement and termination with probability 1 in a permissionless setting. To this end, Gorilla leverages VDFs to extend the approach of Sandglass, the first protocol to provide similar safety guarantees in the presence of benign failures. Neither Gorilla nor Sandglass are practical protocols, however: they exchange a very large number of messages and the number of rounds they require to decide is large even under favorable circumstances, and can, in general, be exponential. Is there a *practical* permissionless protocol that can achieve deterministic safety and tolerate fewer than a half Byzantine nodes?

References

- James Aspnes. Randomized protocols for asynchronous consensus. Distributed Computing, 16(2-3):165–175, 2003.
- [2] James Aspnes, Gauri Shah, and Jatin Shah. Wait-free consensus with infinite arrivals. In Proceedings of the thiry-fourth annual ACM symposium on Theory of computing, pages 524–533, 2002.
- [3] Christian Badertscher, Peter Gaži, Aggelos Kiayias, Alexander Russell, and Vassilis Zikas. Ouroboros genesis: Composable proof-of-stake blockchains with dynamic availability. In *Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security*, pages 913–930, 2018.
- [4] Vivek Bagaria, Sreeram Kannan, David Tse, Giulia Fanti, and Pramod Viswanath. Prism: Deconstructing the blockchain to approach physical limits. In Proceedings of the 2019 ACM SIGSAC Conference on Computer and Communications Security, pages 585–602, 2019.
- [5] Gilles Barthe, Joost-Pieter Katoen, and Alexandra Silva. Foundations of Probabilistic Programming. Cambridge University Press, 2020.
- [6] Dan Boneh, Joseph Bonneau, Benedikt Bünz, and Ben Fisch. Verifiable delay functions. In Annual international cryptology conference, pages 757– 788. Springer, 2018.
- [7] Phil Daian, Rafael Pass, and Elaine Shi. Snow white: Robustly reconfigurable consensus and applications to provably secure proof of stake. In Financial Cryptography and Data Security: 23rd International Conference, FC 2019, Frigate Bay, St. Kitts and Nevis, February 18–22, 2019, Revised Selected Papers 23, pages 23–41. Springer, 2019.
- [8] Soubhik Deb, Sreeram Kannan, and David Tse. Posat: proof-of-work availability and unpredictability, without the work. In Financial Cryptography and Data Security: 25th International Conference, FC 2021, Virtual Event, March 1-5, 2021, Revised Selected Papers, Part II 25, pages 104– 128. Springer, 2021.
- [9] Cynthia Dwork, Nancy Lynch, and Larry Stockmeyer. Consensus in the presence of partial synchrony. *Journal of the ACM (JACM)*, 35(2):288–323, 1988.
- [10] Cynthia Dwork and Moni Naor. Pricing via processing or combatting junk mail. In Proceedings CRYPTO '92: 12th International Cryptology Conference, pages 139–147. Springer, 1992.
- [11] Matthias Fitzi, Peter Ga, Aggelos Kiayias, and Alexander Russell. Parallel chains: Improving throughput and latency of blockchain protocols via parallel composition. *Cryptology ePrint Archive*, 2018.

- [12] Yossi Gilad, Rotem Hemo, Silvio Micali, Georgios Vlachos, and Nickolai Zeldovich. Algorand: Scaling byzantine agreements for cryptocurrencies. In Proceedings of the 26th symposium on operating systems principles, pages 51–68, 2017.
- [13] Jean Jacod and Philip Protter. Probability essentials. Springer Science & Business Media, 2004.
- [14] Markus Jakobsson and Ari Juels. Proofs of work and bread pudding protocols. In Secure Information Networks, pages 258–272. Springer, 1999.
- [15] Benjamin Lucien Kaminski. Advanced weakest precondition calculi for probabilistic programs. PhD thesis, RWTH Aachen University, 2019.
- [16] Rami Khalil and Naranker Dulay. Short paper: Posh proof of staked hardware consensus. Cryptology ePrint Archive, 2020.
- [17] Aggelos Kiayias, Alexander Russell, Bernardo David, and Roman Oliynykov. Ouroboros: A provably secure proof-of-stake blockchain protocol. In Advances in Cryptology-CRYPTO 2017: 37th Annual International Cryptology Conference, Santa Barbara, CA, USA, August 20–24, 2017, Proceedings, Part I, pages 357–388. Springer, 2017.
- [18] Andrew Lewis-Pye and Tim Roughgarden. Resource pools and the cap theorem. arXiv preprint arXiv:2006.10698, 2020.
- [19] Andrew Lewis-Pye and Tim Roughgarden. Byzantine generals in the permissionless setting, 2021. URL: https://arxiv.org/abs/2101.07095, doi:10.48550/ARXIV.2101.07095.
- [20] Jieyi Long. Nakamoto consensus with verifiable delay puzzle. arXiv preprint arXiv:1908.06394, 2019.
- [21] Dahlia Malkhi, Atsuki Momose, and Ling Ren. Byzantine consensus under fully fluctuating participation. *Cryptology ePrint Archive*, 2022.
- [22] Michael Mirkin, Lulu Zhou, Ittay Eyal, and Fan Zhang. Sprints: Intermittent blockchain pow mining. *Cryptology ePrint Archive*, 2023.
- [23] Atsuki Momose and Ling Ren. Constant latency in sleepy consensus. In Proceedings of the 2022 ACM SIGSAC Conference on Computer and Communications Security, pages 2295–2308, 2022.
- [24] Satoshi Nakamoto. Bitcoin: A peer-to-peer electronic cash system. Decentralized Business Review, page 21260, 2008.
- [25] Joachim Neu, Ertem Nusret Tas, and David Tse. Ebb-and-flow protocols: A resolution of the availability-finality dilemma. In 2021 IEEE Symposium on Security and Privacy (SP), pages 446–465. IEEE, 2021.

- [26] Rafael Pass, Lior Seeman, and Abhi Shelat. Analysis of the blockchain protocol in asynchronous networks. In Advances in Cryptology – EURO-CRYPT 2017 - 36th Annual International Conference on the Theory and Applications of Cryptographic Techniques, Proceedings, Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), pages 643–673. Springer Verlag, 2017.
- [27] Rafael Pass and Elaine Shi. The sleepy model of consensus. In Advances in Cryptology-ASIACRYPT 2017: 23rd International Conference on the Theory and Applications of Cryptology and Information Security, Hong Kong, China, December 3-7, 2017, Proceedings, Part II 23, pages 380–409. Springer, 2017.
- [28] Youer Pu, Lorenzo Alvisi, and Ittay Eyal. Safe Permissionless Consensus. In Christian Scheideler, editor, 36th International Symposium on Distributed Computing (DISC 2022), volume 246 of Leibniz International Proceedings in Informatics (LIPIcs), pages 33:1–33:15, Dagstuhl, Germany, 2022. Schloss Dagstuhl – Leibniz-Zentrum für Informatik. URL: https://drops.dagstuhl.de/opus/volltexte/2022/17224, doi: 10.4230/LIPIcs.DISC.2022.33.
- [29] Youer Pu, Lorenzo Alvisi, and Ittay Eyal. Safe permissionless consensus. Cryptology ePrint Archive, Paper 2022/796, 2022. https://eprint.iacr. org/2022/796. URL: https://eprint.iacr.org/2022/796.
- [30] Ronghua Xu and Yu Chen. Fairledger: a fair proof-of-sequential-work based lightweight distributed ledger for iot networks. In 2022 IEEE International Conference on Blockchain (Blockchain), pages 348–355. IEEE, 2022.

A Sandglass Plus

In this section, we first introduce the SM+ model, which is nearly identical to that of Sandglass [29], with the exception that it permits defective nodes to receive messages sent by other defective nodes within the same step, subject to certain constraints.

We then prove that Sandglass remains correct in this new model by satisfying Validity, Agreement, and termination with probability 1. Fortunately, the correctness proof of Sandglass requires only minor modifications to the proofs of two lemmas to be applicable to the SM+ model. We will show in Section A.3 the two lemmas that require change, and refer the readers to the Sandglass paper for the rest of the proof.

A.1 The SM+ Model

SM+ and the Sandglass model (SM) largely make the same set of assumptions. We show the only difference here and refer the readers to the rest of the model

in the Sandglass paper [29]: SM assumes that if in step t a node p_i receives message m with Receive_i, then m was sent in some step t' < t. In SM+, we weaken this assumption, by allowing defective nodes to non-recursively receive messages sent from defective nodes within the same step. Formally, if in step t a node p_i receives message m from p_j with Receive_i, then m was sent in some step t' < t when at least one of p_i and p_j is good, or $t' \leq t$ when both p_i and p_j are defective and m does not contain in its coffer a message that is also sent in s.

A.2 Sandglass protocol

We run Sandglass protocol (Algorithm 2) in SM+.

Protocol 2	Sandgl	ass: Code	e for	node p_i
------------	--------	-----------	-------	------------

1: procedure $INIT(input_i)$ $v_i \leftarrow input_i; \ priority_i \leftarrow 0; \ uCounter_i \leftarrow 0; \ r_i = 1; \ M_i = \emptyset; \ Rec_i = 0$ 2: $\emptyset; uid_i = 0$ 3: procedure STEP for all $m = (\cdot, \cdot, \cdot, \cdot, \cdot, M)$ received by p_i do 4: $Rec_i \leftarrow Rec_i \cup \{m\} \cup M$ 5: if $\max_{|Rec_i(r)| \ge \mathcal{T}}(r) \ge r_i$ then 6: $r_i = \max_{|Rec_i(r)| \ge \mathcal{T}}(r) + 1$ 7: $M_i = \emptyset$ 8: for all $m = (\cdot, r_i - 1, \cdot, \cdot, \cdot, M) \in Rec_i(r_i - 1)$ do 9: $M_i \leftarrow M_i \cup \{m\} \cup M$ 10: Let C be the multi-set of messages in $M_i(r_i - 1)$ with the largest 11: priority. if all messages in C have the same value v then 12:13: $v_i \leftarrow v$ else14: $v_i \leftarrow \text{one of}\{a, b\}, \text{chosen uniformly at random}$ 15:if all messages in $M_i(r_i - 1)$ have the same value v_i then 16: $uCounter_i \leftarrow 1 + \min\{uCounter|(\cdot, r_i - 1, v_i, \cdot, uCounter, \cdot) \in$ 17: $M_i(r_i - 1)$ else 18: $uCounter_i \leftarrow 0$ 19: $priority_i \leftarrow \max(0, \left|\frac{uCounter_i}{\tau}\right| - 5)$ 20: if $priority_i \geq 6\mathcal{T} + 4$ then 21:22: $Decide_i(v_i)$ $uid_i \leftarrow uid_i + 1;$ 23:24: $M_i \leftarrow M_i \cup Rec_i(r_i)$ broadcast $(p_i, uid_i, r_i, v_i, priority_i, uCounter_i, M_i)$ 25:

A.3 Sandglass is Correct in SM+

The proof of correctness for Sandglass in SM+ closely resembles the proof for SM, with the exception of Lemma 5 and Lemma 11 in the Sandglass paper [29]. While the statements of these lemmas remain unchanged, their proofs require minor modifications.

It is perhaps surprising that so little of the proof needs changing when moving from SM to SM+. The reason is that the original Sandglass proof assumes that all the messages generated by defective nodes contribute to their progress, regardless of when they are actually received. Specifically, when estimating the maximum possible round that defective nodes can be in, the proof considers the totality of messages generated by defective nodes during the execution and divides it by the size of the threshold of messages that must be received to advance to a new round. This best-case scenario for defective nodes already accounts for the additional flexibility that SM+ affords to defective nodes. In particular, the original proof already accounts for the possibility, allowed in SM+, that defective nodes receive, in a given step, messages that defective nodes sent in that same step–even though SM disallows such executions.

In Figure 2, which illustrates the dependency between the statements in the Sandglass paper [29], we highlight Lemma 5 and Lemma 11. The letters L, O, and C, signify Lemma, Observation, and Corollary, respectively.

Lemma 5 in Sandglass [29]. At any step T, any defective node is at most one round ahead of any good node.


Proof. By contradiction. Assume that there exists an earliest step, T, where some defective node p is more than one round ahead of a good node p_g , *i.e.*, at T node p is in some round r and node p_g is in round $r_{p_q} \leq (r-2)$.

Note that no good node is in round (r-1) or larger before T; otherwise, by Lemma 3 in Sandglass [29], all good nodes would be in round (r-1) or larger at T, contradicting $r_{p_g} \leq (r-2)$. Therefore, defective node p received no messages from good nodes for round (r-1) by T.

Consider the earliest step $T' \leq T$ where some defective node is in round (r-1). Since T is the first step where some defective node is more than a round ahead of a good node, all good nodes must be in round (r-2) or larger at T'; but, as we just showed, no good node is in round (r-1) or larger before T. Therefore, all good nodes must be in round (r-2) from T' until T.

Consider the k consecutive steps from T' to T. Let the number of messages generated by good nodes and defective nodes in each step be, respectively, $g_1, ..., g_k$ and $d_1, ..., d_k$. Since up to and including step T node p has received for round (r-1) only messages from defective nodes, and yet p is in round r at T, by line 6 of Sandglass, $\sum_{i=1}^{i=k} d_i - 1 \ge \mathcal{T}$ and thus, by Lemma 1 in Sandglass [29], $\sum_{i=2}^{i=k-1} g_i \ge \mathcal{T}$. Since by assumption every step includes at least one good node (*i.e.*, $g_1 > 0$), we have that $\sum_{i=1}^{i=k-1} g_i > \mathcal{T}$. Recall that during these (k-1) steps all good nodes are in round (r-2); then, all messages $g_1, ..., g_{k-1}$ are for round (r-2) and will all be received by all good nodes by T. By line 6 and line 7, then, all good nodes (including p_q) must

Figure 2: The structure of the proof through the dependencies among its constituent lemmas, corollaries, and observations. Preparatory results are in black; red and blue denote facts used in the proofs of Agreement and Termination, respectively. (Taken from Sandglass [29].)



be in round (r-1) at T. This contradicts our assumption and completes the proof.

Lemma 11 in Sandglass [29]. Suppose a good node p_g is in round r at step T, and a node p_d is in round r_d at step $T' \leq T$. If p_d does not collect any messages from good nodes in any round (r-i), where $0 \leq i < kT$, then $r_d \leq (r-(k-1))$.

Proof. To prove the corollary, we compute the maximum number of messages D_{max} that a defective node p_d can collect during the $k\mathcal{T}$ rounds when it does not collect any message from good nodes. To help us count these messages, for any $1 \leq i \leq k\mathcal{T}$, denote by $T_{(r-k\mathcal{T}+i)}$ the earliest step for which all good nodes are at least in round $(r - k\mathcal{T} + i)$.

Recall that, to be collected by p_d at step T', a message from a good node must have been generated no later than step $(T'-1) \leq (T-1)$, and a message from a defective node must have been generated no later than step $T' \leq T$. Then, we partition the execution of the system up to step T into three time intervals, and compute, for each interval, the maximum number of messages generated during these intervals that p_d could have collected for rounds (r - kT + 2) or larger. I1: Up to step $(T_{(r-k\mathcal{T}+1)} - 1)$.

By definition of $T_{(r-k\mathcal{T}+1)}$, some good node is in some round $r' < r - k\mathcal{T} + 1$ at step $(T_{(r-k\mathcal{T}+1)} - 1)$. Therefore, neither a defective node nor a good node can be in some round $r'' > r - k\mathcal{T} + 1$ at step $(T_{(r-k\mathcal{T}+1)} - 1)$, respectively because of Lemma 5 and Corollary 2 in Sandglass [29]. Therefore, during this interval, no messages were generated for rounds $(r - k\mathcal{T} + 2)$ or larger.

I2: From $T_{(r-k\mathcal{T}+1)}$ up to $(T_r - 1)$.

By assumption, p_d only collects messages generated by defective nodes throughout interval I2. We further split I2 into *i* consecutive subintervals, each going from $T_{(r-k\mathcal{T}+i)}$ up to $(T_{(r-k\mathcal{T}+i+1)}-1)$ for $1 \leq i \leq (k\mathcal{T}-1)$. By Lemma 10 in Sandglass [29], in each of these sub-intervals defective nodes can generate at most $(\mathcal{T}-1)$ messages. Therefore, the number of messages generated by defective nodes during I2 is at most $(\mathcal{T}-1) \cdot (k\mathcal{T}-1)$.

I3: From T_r to T.

Once again, by assumption, p_d only collects messages generated by defective nodes throughout interval I3. There are two cases:

-T precedes T_r .

If so, defective nodes trivially generate no messages during I3.

-T does not precede T_r .

By assumption, some good node p_g is in round r at T, where it collects all messages generated by good nodes before T; further, since p_g is still in round r, the messages for round r sent by good nodes before T must be fewer than \mathcal{T} . Finally, since p_g is in round r at T, by Lemma 3 in Sandglass [29], in all steps preceding T no good node can be in round (r+1) or higher. We then conclude that from step T_r and up to (T-1) good nodes generated at most $(\mathcal{T}-1)$ messages, all for round r. Let the number of messages generated by good nodes and defective nodes starting from T_r to T be, respectively, $g_1, ..., g_k$ and $d_1, ..., d_k$. Then we have $\sum_{i=1}^{k-1} g_i < \mathcal{T}$. By Lemma 1 in Sandglass [29], we then have $\sum_{i=1}^{k-1} d_i < \mathcal{T}$, *i.e.*, during I3 defective nodes generate fewer than $(\mathcal{T}-1)$ messages.

Adding the messages generated in the three intervals, we find that D_{max} , the maximum number of messages that p_d could have collected up to and including step T for rounds $(r - k\mathcal{T} + 2)$ or larger, is smaller than $(\mathcal{T} - 1) \cdot k\mathcal{T}$; at the same time, since by assumption p_d is in round r_d , D_{max} must equal at least $(r_d - (r - k\mathcal{T} + 2)) \cdot \mathcal{T}$. Therefore, we have that $(r_d - (r - k\mathcal{T} + 2)) \cdot \mathcal{T} < (\mathcal{T} - 1) \cdot k\mathcal{T}$, which implies $r_d \leq r - (k - 1)$, proving the corollary.

Finally, we have our intended theorem.

Theorem 1. Sandglass satisfies agreement and validity deterministically and termination with probability 1 in SM+.

Proof for the theorem directly follows from Lemma 2, 14, 15 in Sandglass [29].

B Gorilla Correctness

To prove the correctness of Gorilla, we first show a two-step mapping from a Gorilla execution to an execution of Sandglass in SM+ (§B.1). Then, given that Sandglass is correct in SM+, we leverage this mapping to proof safety (§B.2) and liveness (§B.3) for Gorilla.

B.1 Scaffolding

The first step in our two-step process for mapping a Gorilla execution η_G into a Sanglass execution η_S is to reorganize the actions taken by Byzantine nodes in η_G : we want to map η_G to an execution where Byzantine nodes join the system and receive valid messages at the beginning of a step (by the first tick) and broadcast valid messages and leave the system at the step's end (at its *K*-th tick). Since, as explained in Section 5.1, satisfying all of these requirements is not possible, we extend GM to a new model.

We need some way to calculate a VDF on an input that includes the final result of VDF calculations that are still in progress. To achieve this, we extend the oracle's API to allow Byzantine nodes to *peek* at those future outcomes. By issuing the oracle a *peek* query, Byzantine nodes active in any step s can learn the result of a VDF computed by Byzantine nodes finishing at step s before its calculation has ended.

We thus introduce GM+, a model that extends GM by having a new oracle, Ω^+ , that supports one additional method:

Peek(γ): immediately returns vdf_{γ} .

In any tick, a Byzantine node in GM+ can call Peek() multiple times, with different inputs. However, Byzantine nodes can only call Peek subject to two conditions:

- A Byzantine node can peek in step s at vdf_{γ} only if Byzantine nodes commit to finish the VDF calculation for input γ within s; and
- a Byzantine node does not peek at vdf_{γ} , where $\gamma = (M, nonce)$, if M in turn contains some VDF result v obtained by peeking, and the calculation of v has yet to finish in this tick.

Note that these restrictions only limit the *additional* powers that GM+ grants the adversary: in GM+, Byzantine nodes remain strictly stronger than in GM.

With this new model, taking a detour, we first map an execution of Gorilla in GM to an execution of Gorilla in GM+, in which Byzantine behavior is reorganized with the addition of peeking. Hence follows the first lemma of our scaffolding: the existence of the first mapping.

Definition 4. Consider an execution η_G in GM and an execution η_G^+ in GM+. We say η_G and η_G^+ are equivalent iff the following conditions are satisfied:

- **Reorg-1** For every correct node p in η_G , there exists a correct node p^+ in η_G^+ , such that p and p^+ (i) join and leave the system at the same ticks in the same steps and (ii) receive and send the same messages at the same ticks in the same steps.
- **Reorg**-2 Each Byzantine node in η_G^+ (i) joins at the first tick of a step and leaves after the last tick of that step; (ii) receives messages at the first tick of a step and sends messages at the last tick of that step; and (iii) sends and receives only valid messages.
- **Reorg-3** If in η_G a Byzantine node sends a valid message m at a tick in step s, then in η_G^+ a Byzantine node sends m at a tick in some step $s' \leq s$.

Lemma 1. There exists a mapping REORG that maps an execution η_G in GM to an execution η_G^+ in GM+, denoted $\eta_G^+ = \text{REORG}(\eta_G)$, such that η_G is equivalent to η_G^+ .

Proof. Consider any Gorilla execution η_G . We are going to construct an execution η_G^+ in GM+ that satisfies REORG-1,2,3.

First, we specify how correct and Byzantine nodes join and leave in η_G^+ . For each correct node p in η_G , a corresponding correct node p^+ in η_G^+ joins and leaves the system at the same steps as p in η_G . Consider any step s in η_G^+ , and let c be the number of correct nodes in step s. We make (c-1) Byzantine nodes join at the beginning of step s and leave at the end of step s.

Let the set of valid messages sent by Byzantine nodes in η_G be \mathcal{M}_B . Note that this set of valid messages sent by Byzantine nodes can be larger than the set of valid messages correct nodes received from Byzantine nodes due to Byzantine omissions.

Our proof proceeds in two steps. We overview them and then explain them in detail:

Step 1 For any $m \in \mathcal{M}_B$, we assign a unique *shell*, (s, b), identified by a step s and a Byzantine node b in η_G^+ , to the K Get() calls of VDF calculation for m. Note that any node can only make one Get() call in a tick, and it takes K Get() calls to get vdf_m .

We prove four claims about the shells, which are useful later to prove the same messages can be generated in η_G and in η_G^+ .

Step 2 We prove by induction that correct nodes will receive and send the same messages in η_G^+ as in η_G , and the same valid messages are sent by Byzantine nodes at the same step or earlier. Then, it immediately follows that REORG-1,2,3 are satisfied.

Algorithm 3 Algorithm for reorganizing VDF units

1:	procedure Reorg
2:	$s \leftarrow -1$
3:	$CandidateVDFs \leftarrow \emptyset$
4:	loop
5:	$s \leftarrow s + 1; B_s \leftarrow$ the set of Byzantine nodes at step s
6:	$CandidateVDFs \leftarrow CandidateVDFs \cup \{vdf - vdf$'s first unit is cal-
	culated in step s in η_G }
7:	while there's a free shell $(s, p \in B_s)$ do
8:	$vdf \leftarrow$ a VDF result in <i>CandidateVDFs</i> whose last unit is calcu-
	lated the earliest in η_G
9:	Assign (s, p) to vdf
10:	$CandidateVDFs \leftarrow CandidateVDFs \setminus \{vdf\}$

Step 1

We run Algorithm 3 to assign shells for the VDF calculation of messages in \mathcal{M}_B .

Now we prove the following claims are true about the assignment:

Claim 1. For any $m \in \mathcal{M}_B$, if the first Get() call for vdf_m is in step *i*, then the shell assigned to vdf_m in η_G^+ is in step *i* or later.

Proof. Since vdf_m is not added to the *CandidateVDFs* set at line 6 of Algorithm 3 until s is increased to i (in line 5), the step of the shell that vdf_m can be assigned to is at least i (line 9).

Before stepping into Claim 2, we show a useful observation following from Algorithm 3 that is useful to prove Claim 2.

Observation 1. Consider any step s in η_G^+ . We note two possible scenarios of shells at step s, such that if any of these scenarios happens, the calculation of VDFs assigned to shells later than s in η_G^+ must start in a step later than s in η_G :

- A free shell exists at step s in η_G^+ . When the loop for s finishes, if there's a free shell at (s, p), then the CandidateVDFs set is empty at the end of the iteration for s, i.e., for any vdf assigned to a shell in a later step starts its calculation at a step s' > s in η_G .
- A shell at step s is assigned to a vdf that is not the earliest to finish in η_G^+ , among all the vdfs that are not assigned to a shell yet. Consider the scenario in which a vdf is assigned to a shell at s at line 9 (it is the earliest to finish among all VDFs in CandidateVDFs), but it is not the earliest to finish among all the remaining VDFs. Then the calculation of the remaining VDFs, including those VDFs whose calculation is finished earlier than vdf, must start later than s in η_G , because they are not in the CandidateVDFs set yet.

We are ready to prove Claim 2.

Claim 2. For any $m \in \mathcal{M}_B$, if the last Get() call for vdf_m is in step *i*, then the shell assigned to vdf_m in η_G^+ is in step *i* or earlier.

Proof. We prove this by contradiction. Consider the first step i in η_G , such that the last Get() call of a VDF, vdf^* , is in step i, but vdf^* is not assigned to a shell in η_G^+ by the end of i-th iteration of the loop.

Consider the largest step $j \leq i$ such that, one of the scenarios happen in Observation 1. If no such j exists, we take j to be -1. By Observation 1, for all the VDFs that are already assigned to the shells in steps [j+1,i], their first Get() calls are after step j. Furthermore, since they are already assigned to shells, their last unit is no later than vdf^* 's, *i.e.*, their last Get() calls are in or before step i. We call this set of vdfs, VDF_{occupy} . Then, we have all of the Get() calls of VDF_{occupy} are in steps [j+1,i] in η_G .

Note that there are no free shells in [j+1,i] (otherwise, j would be larger). Let the number of Byzantine nodes in any step s be b_s . Then, the size of VDF_{occupy} is $\Sigma_{s=j+1}^i b_s$. Therefore the number of Get() calls for VDF_{occupy} in steps [j+1,i] is $K \cdot \Sigma_{s=j+1}^i b_s$ in η_G .

Note that in η_G , the number of Byzantine nodes at any step s is at most b_s . Therefore, the total number of Get() calls that can be made in steps [j+1, i] in η_G is at most $K \cdot \sum_{s=j+1}^{i} b_s$, and one of them is the last Get() call of vdf^* . Therefore, there are not enough ticks available to make all Get() calls for VDF_{occupy} in η_G . Contradiction.

Claim 3. Consider any two VDFs, vdf_1 and vdf_2 , reserved respectively at steps s_1 and s_2 in η_G^+ . If the last Get() call of vdf_1 is before the first Get() call of vdf_2 in η_G , then $s_1 \leq s_2$.

Proof. By line 6, vdf_2 must be added to the CandidateVDFs set after vdf_1 . By line 8, vdf_1 must be assigned to its shell before vdf_2 . Note that, by line 5, shells are assigned in non-decreasing step order; therefore, $s_1 \leq s_2$.

Claim 4. Consider any three vdf_s , vdf_1 , vdf_2 , and vdf_3 , reserved respectively at steps s_1 , s_2 and s_3 in η_G^+ . If, in η_G , the last Get() call of vdf_1 is before the first Get() call of vdf_2 , and the last Get() call of vdf_2 is before the first Get() call of vdf_3 , then $s_1 < s_3$.

Proof. Let the tick of the first Get() call of vdf_2 , and vdf_3 in η_G be t_2^f , and t_3^f .

Note that the last Get() call of vdf_1 is before t_2^f in η_G . By Claim 2, vdf_1 must be assigned to step $\lfloor (t_2^f - 1)/K \rfloor$ or earlier. By Claim 1, vdf_3 must be assigned to $\lfloor t_3^f/K \rfloor$ or later. Since $t_2^f \leq t_3^f - K$, *i.e.*, $(t_2^f - 1) < t_3^f - K$, we have $s_1 \leq \lfloor (t_2^f - 1)/K \rfloor < \lfloor t_3^f/K \rfloor \leq s_3$, *i.e.*, $s_1 < s_3$.

Now in η_G^+ , all the Byzantine nodes join and leave at the boundaries and stay for a single step; and for each valid message m sent by a Byzantine node in η_G , we have assigned a unique shell (s, b) for some s and b^* to it. Then, if b can receive the messages contained in m's message coffer, M_m , then b will make K Get() calls in step s for input $(M_m, nonce_m)$, and therefore b will be able to send m in η_G^+ .

We construct η_G^+ so that if a Byzantine node is able to send a (valid) message m, it sends m to all Byzantine nodes in the next step. Every Byzantine node forwards all the messages it has received in a step to all the Byzantine nodes in the next step. Furthermore, if m is received at tick t' by a correct node c in η_G , one Byzantine node who has m at tick (t'-1) will send m to c at tick (t'-1) in η_G^+ .

We will show in Step 2 that for each valid message m sent by a Byzantine node in η_G and the shell (s, b) assigned to it, b can indeed receive the messages contained in m's message coffer, and can therefore send m at s. Furthermore, any correct node c^+ at step s in η_G^+ can receive the same set of messages as its corresponding node c in η_G at step s, and therefore send the same message at s.

Step 2

We will prove by induction that we can construct η_G^+ such that any message received and sent in η_G by correct nodes will be received and sent in η_G^+ at the same step, and any valid message sent in η_G by Byzantine nodes will be sent in η_G^+ at the same or earlier step to Byzantine nodes and be sent in the same step as in η_G to correct nodes.

Recall that in GM+, Byzantine nodes can peek VDF result of other Byzantine nodes that in the same step.

Base case In step 0, we show it is possible to (i) make all correct nodes in η_G^+ send the same messages sent by their corresponding correct nodes in η_G at step 0, and (ii) for any shell $(0, p_{sh})$ that is reserved for message m_{sh} , make p_{sh} send m_{sh} .

First, consider the valid messages that are sent by correct nodes in step 0 in η_G . In step 0, since there are not enough ticks to generate a VDF; therefore, all correct nodes receive no (valid) message in η_G , *i.e.*, the message coffer of any valid message sent by correct nodes in step 0 in η_G is empty. Therefore, by making all the correct nodes have the same initial values as in η_G and pick the same nonces, any (valid) message sent in η_G can also be sent in η_G^+ in step 0.

Second, consider any message m_{sh} whose shell is in step 0 in η_G^+ . Consider the message coffer M_{sh} of m_{sh} . Note that in η_G , for any $m \in M_{sh}$, m's last Get() call must be before m_{sh} 's first Get() call. Therefore, by Claim 3, m's shell must also be in step 0. Since step 0 is the earliest step, by Claim 4, m does not contain any messages in its message coffer, otherwise messages in m's message coffer would have been assigned to a step earlier than step 0. Then, p^+ can include the messages in M_{sh} in its message coffer in η_G^+ by peeking the vdf_m , therefore, p^+ can send m_{sh} in step 0. Again, by picking the same nonce, m_{sh} can be sent in η_G^+ in step 0.

We make the nodes send these messages in η_G^+ in the following way:

- Correct nodes send their messages to all the nodes.
- Byzantine nodes send their messages to all the Byzantine nodes.
- Consider a correct node p_c that receives a message m sent by a Byzantine node in η_G at step 1. Note that by Claim 2, m must be assigned to a shell in step 0. Let that shell be $(0, b_m)$. b_m sends m to p_c at step 0 in η_G^+ .
- **Induction hypothesis** Up until step k, any message sent in η_G by a correct node is sent in η_G^+ at the same step. Byzantine nodes can send all the messages whose shells are at step K. Messages received by correct nodes up until step (k + 1) are the same as in η_G . Byzantine nodes receive all the messages from correct nodes and Byzantine nodes.

Induction step Consider messages sent at step (k+1) in η_G .

First, we prove correct nodes can send the same messages in step (k + 1)in η_G^+ as in η_G . By induction hypothesis and synchrony, correct nodes receive the same set of messages from Byzantine nodes and correct nodes in step (k + 1) in η_G^+ as in η_G . By making all the correct nodes select the same nonces in η_G^+ as in η_G , correct nodes are going to send the same messages in η_G^+ as in η_G .

Second, we prove that Byzantine nodes can send all the messages whose shells are at step (k + 1) in η_G^+ . Consider any message m_{sh} whose shell is at step (k + 1), and any m_M in m_{sh} 's message coffer in η_G . There are two possibilities for m_{sh} .

- m_M is sent by a Byzantine node Then the last Get() call for VDF of m_M is before the first Get() call for VDF of m_{sh} in η_G . Then, by Claim 3, the shell reserved for m_M is in a step s_M , where $s_M \leq (k+1)$. Note that in η_G^+ , Byzantine nodes in a step can peek VDF results for messages from Byzantine nodes that will finish within the same step; and, by Claim 4, m_M does not contain any message whose shell is also in step (k + 1) or later. It follows that m_M can be included in the message coffer of m_{sh} in η_G^+ .
- m_M is sent by a correct node By Claim 1, m_{sh} is calculated no later than step (k + 1) in η_G . Therefore, m_M must be sent in a step no later than step k in η_G . By the induction hypothesis, m_M is sent in η_G^+ . Therefore, m_M can be included in m_{sh} 's coffer in η_G^+ .

Therefore, by picking the same nonces, Byzantine nodes can also send the same messages as in η_G at step (k+1) in η_G^+ whose shells are at step (k+1).

We make the nodes send above messages in η_G^+ in the following way:

- Correct nodes send their messages to all the nodes.
- Byzantine nodes send their messages to all the Byzantine nodes.
- Byzantine nodes forward messages they received to all the Byzantine nodes.
- Consider a correct node p_g that receives a message m sent by a Byzantine node in η_G at step (k+2). By Claim 2, m must be assigned to a shell that is no later than (k+1). We just showed above that Byzantine nodes can send all the messages whose shells are at step (k+1). Combining with induction hypothesis, some Byzantine node b_m must have received or generated m. b_m sends m to p_g at step (k+1) in η_G^+ .

Now we have proven that correct nodes receive and send the same messages in η_G as in η_G^+ . Note that we also proved that Byzantine nodes can send all the messages at the step where their shells are. By Claim 2, it directly follows that for any valid message *m* sent by a Byzantine node in η_G , a Byzantine node sends the same messages in the same step or earlier in η_G^+ (REORG-3).

In summary, we have constructed η_G^+ in GM+ that satisfies Reorg-1,2,3.

While peeking solves the challenge with reorganizing Byzantine behavior, it complicates our second mapping. The ability to peek granted to Byzantine nodes in GM+ has no equivalent in Sandglass – it simply cannot be reduced to the effects of network delays or to the behavior of defective nodes. Therefore, we weaken SM so that defective nodes can benefit from a capability equivalent to peeking.

We do so by introducing SM+, an extension of SM that is identical to SM, except for the following change: defective nodes at step s can receive any message m sent by a defective node no later than s – as opposed to (s - 1) in SM – as long as m does not contain in its coffer a message that is sent at s. Note that allowing defective nodes to receive in a given step a message m sent by defective nodes within that very step maps to allowing Byzantine nodes to peek at a message whose vdf will be finished by Byzantine nodes within the same step; and the constraint that m shouldn't contain in its coffer other messages sent in the same step, maps to the constraint that Byzantine nodes cannot peek at messages whose coffer also contains a peek result from the same step.

One might rightfully ask: was not the plan to leverage the correctness of Sandglass in SM? Indeed, but fortunately, Sandglass still guarantees deterministic agreement and termination with probability 1 under the SM+ model (§A.3). Thus, it is suitable to map a Gorilla execution in GM+ to a Sandglass execution in SM+, and orient our proof by contradiction with respect to the correctness of Sandglass in SM+.

Formally, we specify our second mapping as follows.

Definition 5. Given a message m in the Gorilla protocol, the mapping MAPM produces a message in the Sandglass protocol as follows

- 1. Omit the vdf and the nonce from m.
- 2. Let p_i be the node that sends m. Include p_i as a field in m.
- 3. If m is the j-th message sent by p_i , add a field uid = j to m.
- 4. Repeat the steps above for all of the messages in m's coffer.

Denote the result by $\hat{m} = MAPM(m)$. We say m and \hat{m} are equivalent. Furthermore, with a slight abuse of notation, we apply MAPM to a set of messages as well, i.e., if \mathcal{M} is a set of messages, and we map each message $m \in \mathcal{M}$, we obtain the message set MAPM(\mathcal{M}).

Definition 6. Consider an execution η_G^+ in GM_+ and an execution η_S^+ in SM_+ . We say η_G^+ and η_S^+ are equivalent iff the following conditions are satisfied:

- The nodes in η_G⁺ are in a one-to-one correspondence with the nodes in η_S⁺. For every node p in η_G⁺, we denote the corresponding node in η_S⁺ with p̂.
- 2. Nodes p and \hat{p} join and leave at the same steps in η_G^+ and η_S^+ , respectively. Furthermore, their initial values are the same.
- 3. If p is a Byzantine node, then \hat{p} is defective in SM+; otherwise, \hat{p} is a good node in SM+.
- 4. \hat{p} sends \hat{m} at step s in η_S^+ , iff p generates a message m in η_G^+ at step s. Note that in η_G^+ , correct nodes send their messages to all as soon as they are generated, while Byzantine nodes may only send their messages to a subset of nodes once their messages are generated.
- 5. \hat{p} receives \hat{m} at step s in η_{S}^{+} , iff p receives m at step s in η_{G}^{+} .

Lemma 2. Consider any execution η_G in GM, and an execution η_G^+ in GM+ equivalent to η_G . There exists a mapping INTERPRET that maps η_G^+ to an execution η_S^+ in SM+, denoted as $\eta_S^+ = \text{INTERPRET}(\eta_G^+)$, such that η_S^+ is equivalent to η_G^+ .

Proof. For execution η_G^+ , we construct an equivalent execution η_S^+ in SM+. First, for every p in η_G^+ , we add a corresponding \hat{p} to η_S^+ such that:

- \hat{p} joins and leaves at the same steps that p joins and leaves, respectively.
- \hat{p} has the same initial value as p.
- If p is a Byzantine node, then \hat{p} is a defective node; otherwise, \hat{p} is a good node.

Since the number of Byzantine nodes in a step of η_G^+ is smaller than the number of correct nodes at each step, and the number of defective and good nodes are equal to those of Byzantine and correct nodes, respectively, therefore, the number of defective nodes in η_S^+ is fewer than that of good nodes at each step. Now we have Condition 1, Condition 2 and Condition 3 are satisfied.

We now construct the messages sent in η_S^+ such that η_G^+ and η_S^+ are equivalent. Specifically, we require Condition 4 and Condition 5 in Definition 6 to be satisfied for the messages sent. We prove this by induction on steps. Note that messages are also constructed inductively.

- **Induction Base** Consider any node p in η_G^+ at the first step, and message m that it generates at the first step. We prove the claim for holds for the first step, conditioned on whether p is a correct node or not.
 - p is a correct node Note that p and \hat{p} have the same initial value v_p by construction. We now prove that \hat{p} will send $\hat{m} = \text{MAPM}(m)$ to all nodes at the first step in η_s^+ .

Since there are not enough ticks to generate a VDF, p does not receive any message in the first step, therefore, m does not contain any message in its message coffer. Therefore, $m = (p, r = 1, v = v_p, priority = 0, uCounter = 0, M = \emptyset, \cdot, \cdot)$. Note that \hat{p} can not receive any message in the first step, either. The message \hat{p} sends at the first step, by Sandglass protocol, is $(\hat{p}, uid = 1, r = 1, v = v_p, priority = 0, uCounter = 0, M = \emptyset)$, which is equal to \hat{m} . Note that in η_S^+ , since good nodes are synchronously connected, all the good nodes in the second step will receive \hat{m} . Note that it's possible for a defective node not to receive \hat{m} , by performing an omission failure, or to receive \hat{m} in any step, being asynchronously connected to other nodes.

p is a Byzantine node Note that in SM+, defective nodes at step s can receive any message m sent at s, as long as m does not contain in its coffer a message that is also sent at s. Again, we will prove \hat{m} can and will be sent at the first step in η_S^+ .

We first consider any message m generated by a Byzantine node p, whose message coffer is empty. With the same argument for a correct node p in the first step of η_G^+ , \hat{p} will send \hat{m} in the first step of η_S^+ . Again, note that it's possible for any node not to receive \hat{m} , when \hat{p} performs an omission failure, or to receive \hat{m} in any step, since \hat{p} is asynchronously connected to other nodes.

Second, let's consider a message m generated by a Byzantine node p, whose message coffer is not empty. Note that the number of Byzantine nodes in the first step, which is smaller than \mathcal{T} . We have m = (p, r = $1, v, priority = 0, uCounter = 0, M, \cdot, \cdot)$. Consider any message $m_{pk} \in$ M, m_{pk} must be sent by a Byzantine node and the vdf in m_{pk} is a Peek() result. By specification of Peek(), m_{pk} must be generated in the first step, and not contain any message in its message coffer. We have proven above that \hat{m}_{pk} will be sent in the first step of η_S^+ . Note that message coffer of \hat{m}_{pk} is also empty. Therefore, we make the scheduler deliver \hat{m}_{pk} to the defective node \hat{p} and therefore \hat{p} will include \hat{m}_{pk} in its message coffer. In summary, for every $m_{pk} \in$ M, \hat{p} will receive $\hat{m_{pk}}$, and $|M| < \mathcal{T}$. Therefore, \hat{p} will send (p, r = 1, v, priority = 0, uCounter = 0, MAPM(M)), which is equal to \hat{m} .

- **Induction Hypothesis** \hat{p} receives \hat{m} at step $s' \leq s$ in η_S^+ , iff p receives m at step s' in η_G^+ (Condition 4). \hat{p} sends \hat{m} at step $s' \leq s$ in η_S^+ , iff p generates a message m in η_G^+ at step s' (Condition 5).
- **Induction Step** Now we prove that the claim holds for step s + 1, conditioned on whether p is a correct node or not.
 - p is a correct node We prove Condition 4 and Condition 5 separately.

Condition 4 First, we will prove that if p receives m at step (s+1) in η_G^+ , then \hat{p} receives \hat{m} at step (s+1) in η_S^+ .

If *m* is generated by a correct node p_c , *m* must be sent at step *s* in η_G^+ . By the induction hypothesis, \hat{m} must be sent by a good node \hat{p}_c at step *s* in η_S^+ . Note that in SM+, the network between good nodes is synchronous. Therefore, \hat{p} receives \hat{m} at (s+1) in η_S^+ .

If *m* is generated by a Byzantine node *p*, *m* could have been generated at any step $s' \leq s$ and finally sent to *p* at *s* in η_G^+ . By the induction hypothesis, \hat{m} must be sent by a defective node \hat{p} at step *s'* in η_S^+ . Note that in SM+, the network between good nodes and defective nodes is asynchronous. Therefore, we can make the scheduler deliver \hat{m} to \hat{p} at (s+1) in η_S^+ .

Condition 5 Now we prove that if p generates a message m in η_G^+ at step (s+1), then \hat{p} can send \hat{m} at step (s+1) in η_S^+ . Consider the set of messages Rec_p received by p at s. Note that η_G^+ is equivalent to η_G . Therefore, all the messages sent are valid by Lemma 1. By the induction hypothesis and the proof for Condition 4, \hat{p} received a set of messages MAPM(Rec_p) at step (s+1). Note that Gorilla protocol (in lines 9-11,29) and Sandglass protocol (in lines 8-10,24) construct message coffers in the same way based on the messages received. Let the message coffer maintained by p be M_p . Then, the message coffer \hat{p} has maintained up to (s+1) is MAPM(M_p).

It follows that \hat{p} 's set $C_{\hat{p}}$ at line 11 is MAPM (C_p) . If the proposal value v_p of p is chosen based on vdf at line 20, then \hat{p} also chooses proposal value $v_{\hat{p}}$ based on a random selection at line 15. Then in η_S^+ , \hat{p} chooses the value v_p . Note that any $m_M \in M_p$ and MAPM (m_M) have the same round number, proposal value, priority and uCounter. The variables priority and uCounter are updated the same way in Gorilla (lines 22-25) and in Sandglass (lines 17-20). Therefore, \hat{p} will send message MAPM(m) at s, which has \hat{p} as the process, the same round number, proposal value, priority and uCounter as m, and MAPM (M_p) as the message coffer.

p is a Byzantine node We further separate this case into two sub-cases:

p does not receive a peek result First, we will prove if p receives m at step (s + 1) in η_G^+ , then \hat{p} receives \hat{m} at step (s + 1) in η_S^+ . Since m is not a Peek() result, m must be sent at step s or earlier in η_G^+ . By the induction hypothesis, \hat{m} must be sent at step s or earlier in η_S^+ . Note that in SM+, connections to defective nodes are asynchronous. Therefore, we can make the scheduler deliver \hat{m} to \hat{p} at (s + 1) in η_S^+ .

Now we prove that if p generates a message m in η_G^+ at step (s + 1), then \hat{p} can send \hat{m} at step (s + 1) in η_S^+ .

Consider $m = (r_m, v_m, priority_m, uCounter_m, M_m, nonce_m, vdf_m)$. Note that by Lemma 1, p joins the system for only one step. Therefore, for any $m_M \in M_m$, p receives it at step (s + 1). Therefore, from what we proved above, \hat{p} receives m_M at step (s + 1). Therefore \hat{p} has MAPM (M_m) as its coffer.

Now we prove that \hat{p} can have v_m as proposal value, $priority_m$ as priority, and $uCounter_m$ as uCounter following the Sandglass protocol. Note that by Lemma 1, m must be valid (isValid(m) equals true).

- $uCounter_m$ is 0 For all round $(r_m 1)$ messages in M_m , the largest priority value for proposal values a and b are the same. Therefore, in MAPM (M_m) , the largest priority value for proposal values a and b are the same. Then, it is possible that \hat{p} chooses v_m as its proposal value at line 15.
- $uCounter_m$ is not 0 All round $(r_m 1)$ messages in M_m have the same proposal value v_m . Therefore, in MAPM (M_m) , all round $(r_m - 1)$ messages also propose v_m . By Sandglass protocol (line 12), \hat{p} will set its proposal value to v_m .

Since m is consistent, \hat{p} will set uCounter to uCounter_m and priority to priority_m.

Note that \hat{p} joins the system for only one step, and therefore it sends only one message. We have \hat{p} will send $\hat{m} = (\hat{p}, uid = 1, r_m, v_m, priority_m, uCounter_m, MAPM(M_m)).$

p receives some peek results Consider any peek result m' that p receives at step (s + 1). By constraints on peeking, m' does not contain any peek result, and m' is sent by a Byzantine node within step (s + 1). By what we proved in the first sub-case, $\hat{m'}$ must be sent in step (s + 1). Since in SM+, the defective node \hat{p} can receive m'.

Then, based on the same argument as the first sub-case, we can show that \hat{p} can send \hat{m} .

B.2 Safety

We prove that Gorilla satisfies Validity and Agreement. The proofs follow the same pattern: assume a violation exists in some execution η_G of Gorilla running in GM; map that execution to $\eta_G^+ = \text{Reorg}(\eta_G)$ in GM+; then, map η_G^+ again to $\eta_S^+ = \text{Reorg}(\eta_G^+)$ in SM+; and, finally, rely on the fact that these mappings ensure that correct nodes in η_G and good nodes in η_S^+ reach the same decisions in the same steps to drive a contradiction.

Lemma 3. Consider an arbitrary Gorilla execution η_G , and $\eta_G^+ = \text{REORG}(\eta_G)$. If a correct node p decides a value v at step s in η_G , then p's corresponding node p^+ decides v at step s in η_G^+ .

Proof. Consider any execution η_G in GM and $\eta_G^+ = \text{Reorg}(\eta_G)$ in GM+.

Consider a correct node p that decides a value v at step s in η_G . Consider the message m = (r, v, priority, uCounter, M, nonce, vdf) that p sends right after it decides. Note that by Gorilla protocol, this is the first step that p ever collects at least \mathcal{T} messages for round (r-1) and $priority \ge 6\mathcal{T} + 4$. By Lemma 1, p^+ receives and sends the same messages as p in the same steps. Therefore, s is also the first step that p^+ collects at least \mathcal{T} messages for round (r-1), and p^+ sends m at step s. Therefore, p^+ must also have decided v at step s.

Lemma 4. Consider any execution η_G in GM. If an execution $\eta_G^+ = \text{Reorg}(\eta_G)$ in GM_+ and an execution η_S^+ in SM_+ are equivalent, then the following statements hold:

- 1. If a correct node p decides a value v at step s in η_G^+ , then \hat{p} decides v at step s in η_S^+ .
- 2. Consider the first message m = (r, v, priority, uCounter, M, nonce, vdf)that p generates for round r. Let the step when m is generated be s. If uCounter is 0, then \hat{p} randomly chooses value v as the proposal value at step s in η_S^+ .

Proof. Consider any execution η_G in GM. Consider the equivalent executions $\eta_G^+ = \text{Reorg}(\eta_G)$ in GM+ and η_S^+ in SM+.

Proof for Statement (1): Consider a correct node p that decides a value v at step s in η_G^+ . Consider the message m = (r, v, priority, uCounter, M, nonce, vdf) that p sends right after it decides. Note that by Gorilla protocol, this is the first step that p ever collects at least \mathcal{T} messages for round (r-1) and $priority \ge 6\mathcal{T}+4$. Since η_G^+ and η_S^+ are equivalent, by the definition of equivalence, \hat{p} receives the equivalent messages received by p in the same steps. Therefore, s is also the first step that \hat{p} collects at least \mathcal{T} messages for round (r-1). Note that by definition of equivalence, \hat{p} sends $\hat{m} = (\hat{p}, \cdot, r, v, priority, uCounter, M)$ at s with priority $\ge 6\mathcal{T} + 4$. Then \hat{p} must also have decided v at step s.

Proof for Statement (2): Consider the first message m = (r, v, priority = 0, uCounter = 0, M, nonce, vdf) that p generates for round r, and assume m is generated at step s. By the definition of equivalence, \hat{p} sends $\hat{m} = (\hat{p}, \cdot, r, v, priority = 0, uCounter = 0, M)$ at s in η_S^+ , and \hat{m} is also the first message \hat{p} sent for round r. Since uCounter is 0, v is chosen based on a coin toss by Sandglass protocol. Therefore, \hat{p} must have flipped a coin at step s and the result is v.

Theorem 2. Gorilla satisfies agreement in GM.

Proof. By contradiction, assume that there exists a Gorilla execution η_G in GM that violates agreement. This means that there exist two correct nodes p_1 and p_2 , two steps s_1 and s_2 , and two values $v_1 \neq v_2$ such that p_1 decides v_1 at s_1 and p_2 decides v_2 at s_2 . Consider $\eta_G^+ = \text{REORG}(\eta_G)$. According to Lemma 3, p_1^+ decides v_1 at s_1 and p_2^+ decides v_2 at s_2 , in η_G^+ . Now, consider $\eta_S^+ = \text{INTERPRET}(\eta_G^+)$. According to Lemma 4, \hat{p}_1^+ decides v_1 at s_1 and \hat{p}_2^+ decides v_2 at s_2 , in η_S^+ . However, this contradicts the fact Sandglass satisfies agreement in SM+ (Theorem 1). Therefore, Gorilla satisfies agreement in GM.

Theorem 3. Gorilla satisfies validity in GM.

Proof. By contradiction, assume that there exists a Gorilla execution η_G , such that (i) all nodes that ever join the system have initial value v; (ii) there are no Byzantine nodes; and (iii) a correct node p decides $v' \neq v$.

Since GM+ is an extension of GM, η_G conforms to GM+. According to Definition 4, $\eta_G^+ = \eta_G$ in GM+ is trivially equivalent to η_G . Consider $\eta_S^+ =$ INTERPRET (η_G^+) .

By the construction of the INTERPRET mapping (in Lemma 2), good nodes in η_S^+ have the same initial values as their corresponding correct nodes in η_G . Furthermore, since there are no Byzantine nodes in η_G^+ , there are no defective nodes in η_S^+ by Definition 6. Therefore, by Validity of Sandglass in SM+ (Theorem 1), no good node decides $v' \neq v$. However, by Lemma 3 and Lemma 4, pdecides $v' \neq v$, which leads to a contradiction. Therefore, Gorilla satisfies validity in GM.

B.3 Liveness

Similar to the safety proof, the liveness proof proceeds by contradiction: it starts with a liveness violation in Gorilla, and maps it to a liveness violation in Sandglass.

Formalizing the notion of violating termination with probability 1 requires specifying the probability distribution used to characterize the probability of termination. To do so, we first have to fix all sources of non-determinism [1, 5, 15]. For our purposes, non-determinism in GM and GM+ stems from correct nodes, Byzantine nodes and their behavior; in SM+, it stems from good nodes, defective nodes and the scheduler. For correct, good, and defective nodes, non-determinism arises from the joining/leaving schedule and the initial value of each joining node. For Byzantine nodes in GM and GM+, fixing non-determinism means fixing their action *strategy* according to the current history of an execution. Similarly, fixing the scheduler's non-determinism means specifying the timing of message deliveries and the occurrence of benign failures, based on the current history. We, therefore, define non-determinism formally in terms of an environment and a strategy.

To this end, we introduce the notion of a *message history*, and define what it means for a set of messages exchanged in a given step to be *compatible* with the message history that precedes them.

Definition 7. For any given execution in GM and GM+ (resp., SM+), and any step s, the message history up to s, \mathcal{MH}_s , is the set of $\langle m, p, s' \rangle$ triples such that p is a correct node (resp., good node) and p receives m at $s' \leq s$.

Definition 8. We say a set \mathcal{MP}_{s+1} of $\langle m, p, s+1 \rangle$ triples is compatible with a message history up to s, \mathcal{MH}_s , if there exists an execution such that for any $\langle m, p, s+1 \rangle \in \mathcal{MP}_{s+1}$, the correct node (resp., good node) p receives m at step (s+1).

Definition 9. An environment \mathcal{E} in GM and GM+ (resp., SM+) is a fixed joining/leaving schedule and fixed initial value schedule for correct nodes (resp., good and defective nodes).

Definition 10. Given an environment \mathcal{E} , a strategy $\Theta_{\mathcal{E}}$ for the Byzantine nodes (resp., scheduler) in GM and GM+ (resp., SM+) is a function that takes the message history \mathcal{MH}_s up to a given step s as the input, and outputs a set \mathcal{MP}_{s+1} that is compatible with \mathcal{MH}_s .

Before proceeding, there is one additional point to address. The most general way of eliminating non-determinism is to introduce randomness through a fixed probability distribution over the available options. However, the following lemma, proved in §B.3, establishes that Byzantine nodes do not benefit from employing such a randomized strategy.

Lemma 5. For any environment \mathcal{E} , if there exists a randomized Byzantine strategy for Gorilla that achieves a positive non-termination probability, then there exists a deterministic Byzantine strategy for Gorilla that achieves a positive non-termination probability.

Proof. Let us fix the environment \mathcal{E} . Consider a randomized Byzantine strategy $\Theta_{\mathcal{E}}$ that achieves a positive non-termination probability. We omit \mathcal{E} from the subscript for brevity. Denote the non-termination event in H_{Θ} with NT, *i.e.*, $P_{H_{\Theta}}(NT) > 0$. For brevity, we drop H_{Θ} from the subscripts for the probabilities.

We provide an inductive proof. Consider the first time that a Byzantine node takes a randomized action. This node can only choose from a countable set of actions: sending a message to a node or calculating a unit of VDF. Let us call this set of actions $\mathcal{A} = \{A_1, A_2, \dots\}$. We have $P(NT) = \sum_i P(A_i)P(NT|A_i)$. Now, since P(NT) > 0, there should exist an A_i such that $P(NT|A_i) > 0$, *i.e.*, the Byzantine nodes could have achieved positive non-termination probability by *deterministically* taking the action A_i . Similarly, for every further randomized action with execution prefix ϕ , and with the action choices $\mathcal{A}' = \{A'_1, A'_2, \dots\}$, if $P(NT|\phi) > 0$, then there should exist an A'_i such that $P(NT|\phi, A'_i) > 0$. Repeating this process, we can carve a deterministic strategy from Θ , such that non-termination still has a positive probability. \Box

Since the output vdf of a call to the VDF oracle is a random number, the (vdf mod 2) operation in line 20 of Gorilla is equivalent to tossing an unbiased coin. Given a strategy $\Theta_{\mathcal{E}}$,² the nodes might observe different coin tosses as the execution proceeds; thus, the strategy specifies the action of the Byzantine nodes for all possible coin toss outcomes. The scheduler's strategy in SM+ is similarly specified for all coin toss outcomes. Therefore, once a strategy is determined, it admits a *set* of different executions based on the coin toss outcomes; we denote it by H_{Θ} . Specifically, a strategy determines an action for each outcome of any coin toss.

Given a strategy Θ , we can define a probability distribution $P_{H_{\Theta}}$ over H_{Θ} . For each execution $\eta \in H_{\Theta}$, there exists a unique string of zeros and ones, representing the coin tosses observed during η . Denote this bijective correspondence by COINS : $H_{\Theta} \to \{0, 1\}^* \cup \{0, 1\}^{\infty}$, and the probability distribution on the coin toss strings in COINS (H_{Θ}) by $\tilde{P}_{H_{\Theta}}$. For every event $E \subset H_{\Theta}$, if COINS(E) is measurable in COINS (H_{Θ}) , then $\tilde{P}_{H_{\Theta}}$ (COINS(E)) is well-defined; thus, $P_{H_{\Theta}}(E)$ is also well-defined and $P_{H_{\Theta}}(E) = \tilde{P}_{H_{\Theta}}(\text{COINS}(E))$. We denote $P_{H_{\Theta}}$ as the probability distribution induced over H_{Θ} by its coin tosses.

Equipped with these definitions, we can formally define termination with probability 1.

Definition 11. The Gorilla protocol terminates with probability 1 iff for every environment \mathcal{E} and every Byzantine strategy Θ based on \mathcal{E} , the probability of the termination event T in H_{Θ} , i.e., $P_{H_{\Theta}}(T)$, is equal to 1.

This definition gives us the recipe for proving by contradiction that Gorilla terminates with probability 1. We first assume there exists a Byzantine strategy Θ that achieves a non-zero non-termination probability, and map this strategy through the REORG and INTERPRET mappings to a scheduler strategy Λ that achieves a non-zero non-termination probability in SM+. However, Λ cannot exist, as the Sandglass protocol terminates with probability 1 in SM+ (Theorem 1).

Lemma 6. If there exists an environment \mathcal{E} and a Byzantine strategy $\Theta_{\mathcal{E}}$ in GM that achieves a positive non-termination probability, then there exists an environment \mathcal{E}' and a Byzantine strategy $\Psi_{\mathcal{E}'}$ in GM+ that also achieves a positive non-termination probability.

 $^{^2 \}rm When it is clear from the context, we will omit the environment from the subscript of the strategy.$

Proof. Assume there exist an environment \mathcal{E} and a Byzantine strategy $\Theta_{\mathcal{E}}$ in GM that achieves a positive non-termination probability. Consider the REORG mapping. Since, according to Lemma 1, the joining/leaving and initial value schedules for correct nodes remain untouched by the REORG mapping, we just set $\mathcal{E}' = \mathcal{E}$. In the rest of the proof, we omit the environments for brevity.

We now show that the strategy Ψ exists, and is in fact the same as Θ . For brevity, let R_{Θ} denote REORG (H_{Θ}) , and consider any execution η in H_{Θ} . By Lemma 1, correct nodes in η receive the same messages, at the same steps, as the correct nodes in REORG (η) and, moreover, the coin results in η are exactly the same as the ones in REORG (η) . Thus, the message history of correct nodes up to any step s in η is the same as the message history of correct nodes up to the same step in REORG (η) . In addition, because REORG (η) is a GM+ execution, compatibility is trivially satisfied. Thus, we conclude that Byzantine nodes in R_{Θ} follow the same strategy as in Θ , conforming to the same coin toss process. Let us denote this strategy with Ψ .

Note that according to Lemma 3, whenever a correct node decides at some step s in η , its corresponding correct node in REORG(η) decides the same value at the same step. Therefore, the set of non-terminating executions in H_{Θ} are mapped to the set of non-terminating executions in R_{Θ} in a bijective manner. Let us denote these sets as NT_H and NT_R , respectively. Since the same coin toss process induces probability distributions $P_{H_{\Theta}}$ and $P_{R_{\Theta}}$ on H_{Θ} and R_{Θ} , respectively, we conclude that $P_{H_{\Theta}}(NT_H) = P_{R_{\Theta}}(NT_R)$. Therefore, since $P_{H_{\Theta}}(NT_H) > 0$ by assumption, this concludes our proof, as we have shown the existence of a strategy Ψ in GM+ that achieves a positive non-termination probability.

We can now continue our proof by showing that the INTERPRET mapping preserves the non-zero non-termination probability, which will help us prove our desired liveness property, termination with probability 1. In order to do this, we first introduce a machinery that allows us to prove the perseverance the non-zero non-termination probability throughout the INTERPRET mapping. However, first note that the INTERPRET mapping changes nothing in the executions, and only maps the "syntax" of GM+ to that of SM+. Therefore, the mapping does not introduce non-deterministic decision points for Byzantine nodes. Furthermore, as shown in Lemma 2, actions by Byzantine nodes in any execution in GM+ are translated to actions by the network in SM+. Therefore, we conclude that a Byzantine strategy Θ in GM+ is mapped to a network strategy in SM+. Abusing notation, let us show the mapped strategy with INTERPRET(Θ).

Definition 12. Given strategy Θ for Byzantine nodes (the scheduler message delivery), let NT_{Θ} be the set of executions that do not terminate. Moreover, let us define NT_{Θ}^{i} to be the event where the correct (good) node *i* joins, never leaves and never decides. Similarly, for every $n \in \mathbb{N}$ we define $NT_{\Theta}^{n,i}$ to be the event where the correct (good) node *i* joins, does not leave, and does not decide within the first *n* steps of the execution.

First, note that we can enumerate the correct/good nodes since they are countable. Second, note that our definition of termination in Section 3 implies $NT_{\Theta} = \bigcup_{i=1}^{\infty} NT_{\Theta}^{i}$.

Definition 13. Given a strategy Θ for Byzantine nodes (the scheduler message delivery) in GM+ (SM+), and a correct (good) node i, we define the random variable X_{Θ}^i for each $\eta \in H_{\Theta}$ as follows:

$$X_{\Theta}^{i}(\eta) = \begin{cases} 1 & \text{If } i \text{ joins, never leaves, and never decides during } \eta, \\ 0 & \text{Otherwise.} \end{cases}$$

Furthermore, let us define the random variables $\{X_{\Theta}^{n,i}\}_{n=1}^{\infty}$ as follows:

 $X_{\Theta}^{n,i}(\eta) = \begin{cases} 1 & \text{If } i \text{ joins, does not leave, and does not decide within the first } n \text{ steps during } \eta, \\ 0 & \text{Otherwise.} \end{cases}$

Lemma 8. For every strategy Θ , every correct/good node $i \in \mathbb{N}$, and every $\eta \in H_{\Theta}$, we have $\lim_{n\to\infty} X_{\Theta}^{n,i}(\eta) = X_{\Theta}^i(\eta)$, i.e., $X_{\Theta}^{n,i}$ converges (almost) surely to X_{Θ}^i .

Proof. Consider any execution $\eta \in H_{\Theta}$. If node *i* joins, never leaves, and never decides during η , then for every *n* we have $X_{\Theta}^{i}(\eta) = X_{\Theta}^{n,i}(\eta) = 1$.

If node *i* joins and leaves without deciding, then there exists a step $n_i \in \mathbb{N}$ in which the node leaves. Therefore, for every $n \geq n_i$, we have $X_{\Theta}^i(\eta) = X_{\Theta}^{n,i}(\eta) = 0$. If node *i* joins and decides during η , then there exists an $n_i \in \mathbb{N}$ such that node *i* decides at step n_i . Therefore, for every $n \geq n_i$ we have $X_{\Theta}^i(\eta) = X_{\Theta}^{n,i}(\eta) = 0$.

Based on Lemma 8, and the dominated convergence theorem [13], we have the following lemma.

Lemma 9. For every strategy Θ and every node *i* we have $\lim_{n\to\infty} E\{X_{\Theta}^{n,i}\} = E\{X_{\Theta}^i\}$.

Proof. Based on Lemma 8, the sequence of random variables $\{X_{\Theta}^{n,i}\}$ converges pointwise to X_{Θ}^i . Furthermore, it is clear that every $X_{\Theta}^{n,i}$ is non-negative and bounded from above by 1. This satisfies the conditions required for the dominated convergence theorem, thus the theorem tells us $\lim_{n\to\infty} E\{X_{\Theta}^{n,i}\} = E\{X_{\Theta}^i\}$.

Lemma 10. For every strategy Ψ in GM+, there exists a strategy Λ in SM+ such that $H_{\Lambda} = \{\text{INTERPRET}(\eta) | \eta \in H_{\Psi}\}.$

Proof. We show that the strategy Λ exists, and is in fact the same as Ψ . For brevity, let I_{Ψ} denote INTERPRET (H_{Ψ}) , and consider any execution η in H_{Ψ} . According to Lemma 2, correct nodes in η receive the same messages, at the same steps, as the good nodes in INTERPRET (η) . Thus, the message history

up to any step s in η is the same as the message history up to the same step in INTERPRET(η). In addition, since INTERPRET(η) is an actual SM+ execution, compatibility is trivially satisfied. Thus, we conclude that the executions in I_{Ψ} follow the same strategy as in Ψ . Naming this strategy Λ finishes the proof.

Lemma 7. If there exists an environment \mathcal{E} and a strategy Ψ for Byzantine nodes in GM+ that achieves a positive non-termination probability, then there exists an environment \mathcal{E}' and a scheduler strategy $\Lambda_{\mathcal{E}'}$ in SM+ that also achieves a positive non-termination probability.

Proof. Let us assume that there exists an environment \mathcal{E} and a Byzantine strategy $\Theta_{\mathcal{E}}$ in the Gorilla protocol that leads to a positive non-termination probability. According to Lemma 6, there exists a strategy Ψ in GM+ that achieves a positive non-termination probability, in environment \mathcal{E} . Consider the INTERPRET mapping. Since, according to Lemma 2, the join-ing/leaving and initial value schedules for correct nodes are bijectively mapped by the INTERPRET mapping to the joining/leaving and initial value schedules of the good nodes, respectively, we just set $\mathcal{E}' = \mathcal{E}$. In the rest of the proof, we omit the environments for brevity.

First, note that according to Lemma 4, the INTERPRET mapping preserves all of the coin tosses in H_{Ψ} . Moreover, for a given execution $\eta \in H_{\Psi}$, the same lemma tells us that INTERPRET (η) might include *more* coin tosses than those in η .

Consider $\Lambda = \text{INTERPRET}(\Psi)$, based on Lemma 10. Let us also define the events $NT_{\Psi}, NT_{\Psi}^{i}, NT_{\Lambda}^{n,i}, NT_{\Lambda}, NT_{\Lambda}^{i}$, and $NT_{\Lambda}^{n,i}$ based on Definition 12, for the strategies Ψ and Λ . Since $P_{H_{\Psi}}(NT_{\Psi}) = P_{H_{\Psi}}(\cup_{i=1}^{\infty}NT_{\Psi}^{i})$, using the union bound we have $P_{H_{\Psi}}(NT_{\Psi}) \leq \sum_{i=1}^{\infty} P_{H_{\Psi}}(NT_{\Psi}^{i})$. Now, Ψ achieves a positive non-termination probability, *i.e.*, $P_{H_{\Psi}}(NT_{\Psi}) > 0$. Therefore, there should exist some $i^* \in \mathbb{N}$ such that $P_{H_{\Psi}}(NT_{\Psi}^{i^*}) > 0$, since otherwise we would have $P_{H_{\Psi}}(NT_{\Psi}) = 0$ based on the union bound. We now define the random variables $X_{\Psi}^{i^*}$ and X_{Ψ}^{n,i^*} as in Definition 13, and based on Lemma 9 we have $\lim_{n\to\infty} E\{X_{\Psi}^{n,i^*}\} = E\{X_{\Psi}^{i^*}\}$. Similarly, we define the random variables $X_{\Lambda}^{i^*}$ and X_{Λ}^{n,i^*} , and once again Lemma 9 tells us $\lim_{n\to\infty} E\{X_{\Lambda}^{n,i^*}\} = E\{X_{\Lambda}^{i^*}\}$.

Based on Definition 12, we know that for every n, we have $NT_{\Psi}^{n,i^*} \subset NT_{\Psi}^{n+1,i^*}$ and $NT_{\Lambda}^{n,i^*} \subset NT_{\Lambda}^{n+1,i^*}$. Therefore, we have $E\{X_{\Psi}^{n,i^*}\} = P_{H_{\Psi}}(NT_{\Psi}^{n,i^*}) \leq P_{H_{\Psi}}(NT_{\Psi}^{n+1,i^*}) = E\{X_{\Psi}^{n+1,i^*}\}$ and $E\{X_{\Lambda}^{n,i}\} = P_{H_{\Lambda}}(NT_{\Lambda}^{n,i^*}) \leq P_{H_{\Lambda}}(NT_{\Lambda}^{n+1,i^*}) = E\{X_{\Psi}^{n+1,i^*}\}$. Since the increasing sequence $\{E\{X_{\Psi}^{n,i^*}\}\}_{n=1}^{\infty}$ converges to $E\{X_{\Psi}^{i^*}\} = P_{H_{\Psi}}(NT_{\Psi}^{i^*}) > 0$, there should exist a step n^* such that $P_{H_{\Psi}}(NT_{\Psi}^{n^*,i^*}) = E\{X_{\Psi}^{n^*,i^*}\} > 0$. Now, given n^* , let us consider $P_{H_{\Lambda}}(NT_{\Lambda}^{n^*,i^*}) = E\{X_{\Lambda}^{n^*,i^*}\}$. This value is computed based on the first n^* steps of the executions in H_{Λ} . Based on Lemma 4, we know that these executions contain all of the coin tosses happening in the first n^* steps of the corresponding executions in H_{Ψ} . Moreover, they might contain more coin tosses as explained above. Therefore, if the probability of the event $NT_{\Psi}^{n^*,i^*}$ in H_{Ψ} is positive, the

probability of the corresponding event $NT_{\Lambda}^{n^*,i^*}$ in H_{Λ} should also be positive, *i.e.*, $E\{X_{\Lambda}^{n^*,i^*}\} > 0$. Since the sequence $\{E\{X_{\Lambda}^{n,i^*}\}\}_{n=1}^{\infty}$ is increasing with n and converging to $E\{X_{\Lambda}^{i^*}\}$, we should therefore have $E\{X_{\Lambda}^{i^*}\} > 0$. It immediately follows that $P_{H_{\Lambda}}(NT_{\Lambda}^{i^*}) = E\{X_{\Lambda}^{i^*}\} > 0$. Finally, since $NT_{\Lambda}^{i^*} \subset NT_{\Lambda}$, we should have $0 < P_{H_{\Lambda}}(NT_{\Lambda}^{i^*}) \leq P_{H_{\Lambda}}(NT_{\Lambda})$. This means that Λ is a schedular strategy that achieves positive non-termination

This means that Λ is a scheduler strategy that achieves positive non-termination probability, and finishes our proof.

Theorem 4. The Gorilla protocol terminates with probability 1.

Proof. By contradiction, assume that there exist a GM environment and a Byzantine strategy Θ in Gorilla that achieve a positive non-termination probability. By Lemma 6, there exist a GM+ environment and a strategy Ψ for the Byzantine nodes in GM+ that achieve a positive non-termination probability. Similarly, by Lemma 7, there exists an SM+ environment and a scheduler strategy Λ in SM+ that achieve a positive non-termination probability. But this is a contradiction, since Sandglass terminates with probability 1 in SM+ (Theorem 1). Thus, Byzantine strategy Θ cannot force a positive non-termination probability; Gorilla terminates with probability 1.